

L02622

03305-01A

**WARNING:** Contains Sodium Glyceryl Oleate Phosphate, Dimethyl Ether 115-10-6, and 1,1,2,2-tetrafluoroethane 811-97-2. This product is not defined as flammable by Consumer Product Safety Commission regulations. Do not puncture, incinerate, or store can above 120°F. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Use only in a well ventilated area. Avoid continuous breathing of vapors and mist. Avoid contact with skin and eyes. Overexposure to vapor may cause drowsiness, unconsciousness, respiratory depression and death. Deliberate misuse by concentrating and inhaling the contents can be harmful or fatal. Vapors displace oxygen available for breathing and can cause asphyxiation. Vapors are heavier than air and can collect in low areas, pits, small rooms or the ventilated area. If ventilation is not adequate, respiratory protection should be used. Death can occur without warning if too much is breathed. **FIRST AID:** In case of eye or skin contact, flush with water for 15 minutes. May be harmful or fatal if swallowed. DO NOT induce vomiting. If too much is breathed, remove to fresh air. For severe overexposure call a physician immediately. **DISPOSAL:** All used and unused product should be disposed of in conformance with local, state and federal regulations. For additional information, consult the Material Safety Data Sheet for this product.

KEEP AWAY FROM CHILDREN

To view M.S.D.S.: Tear (DO NOT CUT) label by running a fingernail down between perforations, removing this tab. Fold back label. Do not remove until can is empty.

**Directions: Read entire label before using this product.**

1. For best results, do not overspray
  2. Apply a light, even film to mold surface as needed
  3. To avoid marked parts, do not over apply.
  4. Hold can 10" to 12" from mold surface.
- ELECTRICAL SHOCK HAZARD:** This can will conduct electricity. Keep away from all live electrical sources including Battery Terminals, Solenoids, Electrical Panels and other electronic components. Failure to observe this warning may result in serious injury from electrical shock.

- **RAPID DRYING** anti-stick mold release agent suitable for cold and hot molds
- **PERFECT** for virtually every molding application – the only mold release you need!
- **FOOD-APPROVED RELEASE** yet does not contain silicones or lecithin.
- **COMPLETELY COMPATIBLE** with secondary operations where parts must be painted, stenciled, gilded, bonded, finished, hot stamped or treated; the special cleaning required before part decoration. Permits ultrasonic welding of plastic parts.
- **COMPATIBLE** with certain requirements for molding medical products.
- **4.5% SOLIDS** provide superior lubrication up to 600°F.
- **DOES NOT CONTAIN** CFCs, ODPs or chlorinated solvents.
- **BIOGRADABLE, ODPLESS, NON-FLAMMABLE,** non-staining and non-corrosive.
- **MEETS FDA REGULATION 21 CFR 184.1521** as a direct food additive.
- **PREVENTS STICKING** to increase the life of dies and molds, improve product surface finishes and reduce production times.
- **EXCELLENT FOR USE** in injection and compression molding of ABS, Noryl, nylon, polycarbonate, urethane, acetal, acrylic, polyethylene, polypropylene, polystyrene, polysulfone, PVC and rubber.
- **MATERIAL SAFETY DATA SHEET** printed on back of label for your convenience and safety. (The CRC® MSDS™ is a proprietary label removal system patented under U.S. Patent No. 5,056,827).



**Industrial**

# Universal

## Mold Release

- Paintable
- Fast Drying
- Non-Flammable
- Prevents Sticking
- Non-Silicone, Non-Lecithin
- Meets FDA Reg. 21 CFR 184.1521



01A  
Made in U.S.A.

No. 03305  
Net Wt. 12 oz. (340 g)

**CAUTION: CONTENTS UNDER PRESSURE.**  
Read warnings on back panel.

©2001 CRC Industries, Inc., Warminster, PA 18974  
800-521-9168 (Technical Information)  
800-272-4620 (Customer Service)  
215-442-6260 (MSDS)

Universal Mold Release  
Part # 03305 01A  
Net Wt. 12 oz. (340 g)  
www.crcindustries.com

CAUTION: CONTENTS UNDER PRESSURE.