

L03401

03309-01A

WARNING: Contains Zinc Stearate 557-05-1, Isopropyl 67-53-0, 1-Chloro-1,1-difluoro ethane 75-68-3 and Proprietary Propellant Blend. Do not puncture, incinerate, or store can above 120°F. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Use only in a well ventilated area. Avoid continuous breathing of vapors and mist. Avoid contact with skin and eyes. Overexposure to vapor may cause irritation to eyes and respiratory tract, dizziness and loss of concentration. With high exposure levels, effects can include central nervous system depression and regular heartbeats (cardiac arrhythmia). Product is flammable and should be kept away from all sources of ignition. Vapors are heavier than air and can collect in low areas, pits, small rooms or the ventilated area. If ventilation is not available for breathing, and can cause asphyxiation. Vapors are heavier than air and can collect in low areas, pits, small rooms or the ventilated area. If ventilation is not adequate, respiratory protection should be used. Death can occur without warning if too much is breathed. **FIRST AID:** In case of eye or skin contact, flush with water for 15 minutes. May be harmful or fatal if swallowed. DO NOT induce vomiting. If too much is breathed, remove to fresh air. For severe overexposure call a physician immediately. **DISPOSAL:** All used and unused product should be disposed of in conformance with local, state and federal regulations. For additional information, consult the Material Safety Data Sheet for this product.

KEEP AWAY FROM CHILDREN

To View M.S.D.S.: Tear (DO NOT CUT) label by running a fingernail down between perforations, removing this tab. Fold back label. Do not remove until can is empty.

Directions: Read entire label before using this product.

1. For best results do not overspray.
2. Apply a light, even film to mold surface as needed when sticking occurs.
3. To avoid marked parts, do not over apply.
4. Hold can 10" to 12" from mold surface.

ELECTRICAL SHOCK HAZARD: This can will conduct electricity. Keep away from all live electrical sources including Battery Terminals, Solenoids, Electrical Panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

- **RAPID DRYING** anti-stick mold release agent suitable for cold and hot molds.
- **DRY, LUBRICATING FILM** repels water and does not pick-up dust or dirt.
- **COMPLETELY COMPATIBLE** with secondary operators where parts must be special cleaning required before part decoration.
- **3% SOLIDS** provide effective lubrication up to 600°F.
- **DOES NOT CONTAIN** CFCs or silicones.
- **PREVENTS STICKING** to increase the life of dies and molds, improve product surface finishes and reduce production times.
- **EXCELLENT FOR USE** in injection and compression molding of rubber, polypropylene, polystyrene, ABS, acetal, acrylic, epoxy and phenolic resins, Noryl®, nylon, polycarbonate, polyester, polyethylene and polystyrene. Also for use in powdered metal forming and ceramic molding.
- **MATERIAL SAFETY DATA SHEET** printed on back of label for your convenience and safety. (The CRC® MSDSL™ is a proprietary label removal system patented under U.S. Patent No. 5,056,827).



No. 03309
Net Wt. 11.5 oz. (326 g)

DANGER: FLAMMABLE. CONTENTS UNDER PRESSURE.
Read warnings on back panel.

01A
Made in U.S.A.



Zinc Stearate

Mold Release

Prevents Sticking
Non-Silicone Paintable
Dry, Lubricating Powder
Effective Water Repellent

©2001 CRC Industries, Inc., Warminster, PA 18974
800-272-4620 (Customer Service)
215-442-6280 (MSDS)
Zinc Stearate Mold Release
Part # 03309 01A
Net Wt. 11.5 oz. (326 g)
www.crcindustries.com

DANGER: FLAMMABLE. CONTENTS UNDER PRESSURE.