



# Industrial Long Term Mold Saver

**Corrosion Inhibiting Compound**

**Protects Up to 5 Years Indoors  
Seals Out Corrosion**



**No. 03319  
Net Wt. 10 oz. (284 g)**

**DANGER: EXTREMELY FLAMMABLE  
HARMFUL OR FATAL IF  
SWALLOWED, CONTENTS UNDER PIERCEURE**  
Read warnings on back panel.

**ELECTRICAL SHOCK HAZARD:** This can will conduct electricity. Keep away from all live electrical sources including Battery Terminals, Solenoids, Electrical Panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

**SPECIAL USAGE WARNINGS:** Contents extremely flammable. • Do not spray while spraying. • Extinguish all flames, pilot lights, and heaters. Do not apply while equipment is energized. • Vapors will accumulate readily and may ignite. • Use only with adequate ventilation. • Maintain ventilation during use and until vapors are gone.

- Directions: Read entire label before using this product.**
1. Shake well before using this product.
  2. Best results are obtained when used above 60°F.
  3. Mask area not to be sprayed.
  4. Spray from a distance of 12 to 15 inches in light, even coats.
  5. Allow each coat to dry before applying next coat.
  6. For storage, clean valve by turning can upside down and pressing actuator until only propellant escapes.
  7. Remove with CRC Heavy Duty Mold Cleaner.
  8. Do not apply while equipment is energized.



01A  
Made in U.S.A.  
CRC#4522D

- LONG TERM CORROSION INHIBITOR protects all metal molds with a light amber, transparent film.
- SEALS OUT MOISTURE and corrosive contaminants. Halts rust.
- DRY, SELF-HEALING FILM is highly resistant to humidity and salt spray.
- PROTECTS up to 5 years under normal indoor storage conditions or up to 2 years outdoors.
- MEETS MIL-C-1673 Grade 4, Class 1.
- EXCELLENT FOR USE on all metal molds and dies including plastic, rubber, drawing, stamping, die-casting, fine blanking, stripper plates, jigs and fixtures.
- MATERIAL SAFETY DATA SHEET printed on back of label for your convenience and safety. (The CRC® MSDL™ is a proprietary label removal system patented under U.S. Patent No. 5,056,827).

To view M.S.D.S. Tear (DO NOT CUT) label by running a fingernail down between perforations, removing this tab. Fold back label. Do not remove until can is empty.

**KEEP AWAY FROM CHILDREN**

**WARNING:** Contains Dipropylene glycol monoether/ethyl ether 34590-94-8, Isobutane 107-83-5, n-Hexane 110-54-3, Petroleum Distillate 8052-41-3, Propane 74-99-6, Isobutane 75-28-5, and Dimethyl Ether 36-61-0. Do not breathe vapors. Do not puncture, incinerate, or store can above 120°F. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Product is extremely flammable and should be kept away from all flames and other ignition sources. This product contains chemicals known to the State of California to cause cancer, birth defects and other reproductive harm. Use only in a well ventilated area. Avoid continuous breathing of vapor and other contact with skin and eyes. Overexposure to vapor may cause irritation to eyes and respiratory tract, headaches, dizziness, weakness, numbness and unconsciousness. Slightly irritant to mucous membranes by concentrating and inhaling. The contents can be harmful or fatal. Vapors are heavier than air and can collect in low areas. Vapor may decompose to harmful and corrosive gases when exposed to flame or other heat sources. **FIRST AID:** In case of eye or skin contact, flush with water for 15 minutes. If swallowed, may be harmful or fatal. Do not induce vomiting. If too much is breathed remove to fresh air. If not breathing give artificial respiration. If breathing is difficult, give oxygen. For severe overexposure call a physician immediately. **DISPOSAL:** All used and unused product should be disposed of in conformance with local, state and federal regulations. For additional information, consult the Material Safety Data Sheet for this product.

**DANGER: EXTREMELY FLAMMABLE  
HARMFUL OR FATAL IF SWALLOWED  
CONTENTS UNDER PIERCEURE**

Long Term Mold Saver  
Part # 03319 01A  
Net Wt. 10 oz. (284 g)  
www.crcindustrial.com

©2001 CRC Industries, Inc., Warminster, PA 18974  
800-272-8620 (Customer Service)  
215-442-6288 (MSDS)  
CRC03319D

L02622

03319-01A