



TrueTap

HD Cutting Fluid

- ◆ Use for Extreme Duty Applications
- ◆ Extends Tap & Drill Life
- ◆ Thick Fluid Sticks to the Tool

Part No. 03401

Net Contents 1 gallon (3.78 L)

Read Warnings on Back Panel

CRC TrueTap HD Cutting Fluid

An extreme duty cutting fluid. It is a thick fluid that sticks to the cutting tool throughout the operation. Considered environmentally safe.

This fluid is ideal for tapping and drilling stainless steel, carbon steel, inconel, monel, hastalloy, titanium, aluminum and other alloys and exotics.

- Increases productivity
- Extends tool life
- Provides excellent finish and accurate threads
- Will not evaporate

WARNING: Contains Chlorinated Paraffin 63449-39-8, Methyl Salloylate 119-36-8, Petroleum Distillate 64742-53-6 and Glycerol ester of fatty acid (proprietary). Do not use near fire or open flame. Use only in a well ventilated area. Avoid breathing mist, may cause irritation of the respiratory tract. Avoid contact with eyes and skin.

FIRST AID: In case of eye or skin contact flush with water for 15 minutes. If swallowed, may be harmful or fatal. Do not induce vomiting. If too much is breathed, remove to fresh air. For severe overexposure, call a physician immediately. For additional information, consult the Material Safety Data Sheet for this product.

DIRECTIONS: Read entire label before using this product. Apply to tool before coming in contact with the work, using only enough to coat the tool. After cutting, use a CRC Cleaner/Degreaser and a CRC corrosion inhibitor to clean and protect parts.

All used and unused product should be disposed of in accordance with local, state and federal regulations.

KEEP AWAY FROM CHILDREN

©2001 CRC Industries, Inc.
Made in U.S.A.
Warminster, PA 18974
800-521-3168 (Technical Information)
800-272-4620 (Customer Service)
215-442-6260 (MSDS)
www.crcindustries.com
01A

