



TrueTap LV Cutting Fluid



- ◆ **Heavy Duty Applications**
- ◆ **Can Be Used As A Circulating Fluid**
- ◆ **Greatly Extends Tap & Drill Life**

Part No. 03421

Net Contents 1 gallon (3.78 L)

Read Warnings on Back Panel



TrueTap LV Cutting Fluid

True Tap LV is a light viscosity fluid designed for heavy duty tapping and cutting. Due to its light viscosity, it can be used in a sump and circulated through traditional coolant pumps. When used in conjunction with a coolant, True Tap LV will float on the coolant and can be skimmed to prevent contamination. Works on ferrous and non-ferrous metals.

WARNING: Contains Petroleum Distillate 64742-53-6, Chlorinated Paraffin 63449-39-8, Methyl Salicylate 119-36-8 and Glycerol ester of fatty acid (Proprietary). Do not use near fire or open flame. Use only in a well ventilated area. Avoid breathing mist, may cause irritation of the respiratory tract. Avoid contact with eyes and skin.

DIRECTIONS: Read entire label before using this product. Apply to tool before coming in contact with the work, using only enough to coat the tool. After cutting, use a CRC Cleaner/Degreaser and a CRC corrosion inhibitor to clean and protect parts.

All used and unused product should be disposed of in accordance with local, state and federal regulations.

KEEP AWAY FROM CHILDREN

FIRST AID: In case of eye or skin contact flush with water for 15 minutes. If swallowed, may be harmful or fatal. Do not induce vomiting. If too much is breathed, remove to fresh air. For severe overexposure, call a physician immediately. For additional information, consult the Material Safety Data Sheet for this product.



©2001 CRC Industries, Inc.
Made in U.S.A.
Warminster, PA 18974
800-521-3168 (Technical Information)
800-272-4620 (Customer Service)
215-442-6260 (MSDS)
www.crcindustries.com
01A