



TrueTap^{EV} Cutting Fluid



- ◆ Replaces 1,1,1-Trichloroethane
- ◆ Superior Finish and Threads
- ◆ Evaporates Quickly
- ◆ Leaves No Residue

Part No. 03451

Net Contents 1 gallon (3.78 L)

DANGER: VAPOR HARMFUL.
Read Warnings on Back Panel



TrueTap^{EV} Cutting Fluid

- TAPPING
- BORING
- MILLING

- DRILLING
- TURNING
- BROACHING

- REAMING
- THREADING
- SAWING

A solvent based cutting fluid designed to replace 1,1,1 Trichloroethane based cutting fluids. It delivers equivalent performance without being labeled as a suspected ozone-depleting agent.

True Tap EV has been tested side-by-side with 1,1,1 Trichloroethane based cutting fluids. Results showed equal performance on materials such as stainless steel, monel, and hastelloy. True Tap EV evaporates quickly, leaves no residue, and provides excellent finishes.

WARNING: Contains Trichloroethylene 79-01-06 and Petroleum Hydrocarbon 64742-52-5. Harmful if inhaled. Overexposure can cause eye and skin irritation, irritation to upper respiratory tract, central nervous system effects, irregular heartbeats, unconsciousness and death. Deliberate misuse by concentrating and inhaling the contents can be harmful or fatal. This product has no flash or fire point at normal handling temperatures. In high concentrations, this product can be made to burn. Do not use on energized equipment or near flames or arcs. This product contains a chemical known to the State of California to cause cancer, birth defects and other reproductive harm. Use only in a well ventilated area. Avoid continuous breathing of vapor and spray mist. Avoid contact with the skin and eyes. Vapors are heavier than air and can collect in low areas. If ventilation is not adequate, respiratory protection should be used.

FIRST AID: In case of eye or skin contact, flush with water for 15 minutes. If swallowed may be harmful or fatal. Do not induce vomiting. If too much is breathed, remove to fresh air. For severe overexposure call a physician immediately. For additional information, consult the Material Safety Data Sheet for this product.

DIRECTIONS: Read entire label before using this product. Apply to tool before coming in contact with the work, using only enough to coat the tool. After cutting, use a CRC Cleaner/Degreaser and a CRC corrosion inhibitor to clean and protect parts.

All used and unused product should be disposed of in accordance with local, state and federal regulations.

KEEP AWAY FROM CHILDREN



©2001 CRC Industries, Inc.
Made in U.S.A.

Warminster, PA 18974
800-521-3168 (Technical Information)
800-272-4620 (Customer Service)
215-442-6260 (MSDS)
www.crcindustries.com
01A