



# TrueTap

## AL Cutting Fluid

- ◆ Superior Cooling & Lubricity in Cutting Aluminum
- ◆ Evaporates Quickly
- ◆ Extends Tap & Drill Life

Part No. 03461

Net Contents 1 gallon (3.78 L)

**DANGER: HARMFUL OR FATAL IF SWALLOWED.**  
Read Warnings on Back Panel



## TrueTap AL Cutting Fluid

A solvent based cutting fluid. It delivers equivalent performance without being labeled as a suspected ozone-depleting agent.

Designed to provide superior lubricity and cooling in cutting aluminum and its alloys. Evaporates quickly, leaves very little residue, and provides excellent finishes.

**WARNING:** Contains Hydrotreated Light Distillate 64742-47-8 and Glycerol Ester of fatty acid (Proprietary).

Do not use near fire or open flame. Use only in a well ventilated area. Avoid breathing mist, may cause irritation of the respiratory tract. Avoid contact with eyes and skin.

**FIRST AID:** In case of eye or skin contact, flush with water for 15 minutes. If swallowed may be harmful or fatal. Do not induce vomiting. If too much is breathed, remove to fresh air. For severe overexposure call a physician immediately. For additional information, consult the Material Safety Data Sheet for this product.

**DIRECTIONS:** Read entire label before using this product. Apply to tool before coming in contact with the work, using only enough to coat the tool. After cutting, use a CRC Cleaner/Degreaser and a CRC corrosion inhibitor to clean and protect parts.

All used and unused product should be disposed of in accordance with local, state and federal regulations.

**KEEP AWAY FROM CHILDREN**



©2001 CRC Industries, Inc.  
Made in U.S.A.  
Warminster, PA 18974  
800-521-3168 (Technical Information)  
800-272-4620 (Customer Service)  
215-442-6260 (MSDS)  
[www.crcindustries.com](http://www.crcindustries.com)  
01A