



# TrueTap™ AL Cutting Fluid

■ Superior Cooling & Lubricity in Cutting Aluminum

Part No. 03463

NET WEIGHT: 379.5 lbs (172 Kg)

**HANDLING AND SPILL PRECAUTIONS:** Keep container closed. Wash thoroughly after handling. Do not enter where vapors are suspected in high concentration unless air-supplied positive pressure breathing apparatus is used and a trained observer is present and equipped with rescue gear. Vapors of this product may develop a flammable atmosphere. Keep away from flames, sparks, or other ignition sources. Do not cut or weld containers due to explosion hazard. **FOR SPILLS,** use proper protective equipment. Take precautions as necessary to prevent contamination of ground or surface water. For small spills, use absorbent and sweep into closed containers for disposal. For large spills, evacuate the area, dike and transfer into containers for disposal. **DISPOSAL:** Used and unused contents and containers must be disposed of in accordance with all federal, state, and local regulations. **EMPTY** containers may be offered to a qualified reconditioner. Unused contents may be offered to a licensed reclaimer. Do not dump into sewers, on the ground, or into any body of water.

**FIRST AID:** In case of eye or skin contact, flush with water for 15 minutes. If swallowed, **DO NOT** induce vomiting. If too much is breathed, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. For severe overexposure, call a physician immediately.

**CAUTION:** Empty containers retain residue (liquid and/or vapor) and can be dangerous. **DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE THIS CONTAINER TO HEAT, FLAME, SPARKS, OR OTHER SOURCES OF IGNITION: IT MAY EXPLODE AND CAUSE INJURY OR DEATH.** Do not attempt to clean, since residue is difficult to remove. Empty drums should be completely drained, promptly bunged, and promptly returned to a drum reconditioner.

Use only in a well ventilated area. For additional information, consult the Material Safety Data Sheet for this product.

Outstanding lubricity and cooling properties designed specifically for use in cutting aluminum and its alloys.

**WARNING:** Contains Hydrotreated Light Distillate 64742-47-8 and Glycerol Ester of fatty acid (Proprietary).

### HAZARDOUS MATERIAL IDENTIFICATION SYSTEM

HEALTH	<b>1</b>	REACTIVITY	<b>1</b>
FLAMMABILITY	<b>2</b>	PERSONAL PROTECTION	<b>B</b>

HAZARD: MINIMAL=0 SEVERE=4

KEEP OUT OF REACH OF CHILDREN

**DANGER:HARMFUL OR FATAL IF SWALLOWED.**  
Read warnings carefully.

©2002 CRC Industries, Inc.  
Warminster, PA 18974  
800-521-3168 (Technical information)  
800-272-4620 (Customer Service)  
215-442-6260 (MSDS)  
www.crcindustries.com  
02A Made in U.S.A.  
FOR EMERGENCIES CALL CHEMTREC  
1-800-424-9300

