



TrueTap



- ◆ **Excellent EP Properties & Lubricity**
- ◆ **Can Be Used With All Drop Applicators**
- ◆ **Low Vapor Pressure & Non Objectionable Odor**

Part No. 03471

Net Contents 1 gallon (3.78 L.)

Read Warnings on Back Panel



TrueTap EP Cutting Fluid

An extreme duty fluid for very difficult machining and stamping applications. This product provides excellent EP, anti-wear, lubricity and boundary film lubrication.

The product is very effective in drilling, tapping, milling, turning, stamping and drawing on both ferrous and nonferrous materials. Provides temporary in-process corrosion inhibition for copper and its alloys.

WARNING: Contains Triglycerides (Proprietary) and Phosphatized Telomer (Proprietary).

Do not use near fire or open flame. Use only in a well ventilated area. Avoid breathing mist, may cause irritation of the respiratory tract. Avoid contact with eyes and skin.

FIRST AID: In case of eye or skin contact flush with water for 15 minutes. If swallowed, may be harmful or fatal. Do not induce vomiting. If too much is breathed, remove to fresh air. For severe overexposure, call a physician immediately.

For additional information, consult the Material Safety Data Sheet for this product.

DIRECTIONS: *Read entire label before using this product.* Use Full Strength. Do not dilute. Can be used with all drop applicators. After cutting, use a CRC Cleaner/Degreaser and a CRC corrosion inhibitor to clean and protect parts.

All used and unused product should be disposed of in accordance with local, state and federal regulations.

KEEP AWAY FROM CHILDREN



©2001 CRC Industries, Inc.
Made in U.S.A.
Warminster, PA 18974
800-521-3168 (Technical Information)
800-272-4620 (Customer Service)
215-442-6260 (MSDS)
www.crcindustries.com
01A