



URETHANE SEAL COAT

- INSULATES electronic and electrical equipment and components.
- RESISTS abrasion.
- SEALS OUT water and moisture.
- HIGH DI-ELECTRIC STRENGTH, high surface and volume resistivity.
- MAINTAINS electrical characteristics over a temperature range of -90°F to +250°F.
- This product may not be suitable for use on sensitive plastics. Test on small area before use.

Directions: Read entire label before using this product.

1. Clean surface thoroughly with a CRC Cleaner/Degreaser or Precision Cleaner.
2. Mask area not to be sprayed.
3. Best results are obtained when sprayed above 60° F. Spray from 12 - 15 inches away in light, even coats.
4. Additional coats for heavy film can be applied when first coat is dry. For maximum adhesion, apply additional coats in less than 48 hours.
5. When finished spraying, clean valve by turning can upside down and pressing button until only pressure escapes. If clogging occurs, remove button and clean slot and orifice with fine wire.
6. Do not use on energized equipment.

All used and unused product should be disposed of in conformance with local, state and federal regulations.

ELECTRICAL SHOCK HAZARD: This can will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

HMIS: Health: 3 Flammability: 4 Reactivity: 0 PPE: B

WARNING: Contains Isocyanate 107-83-5, n-Hexane 110-54-3, Xylene 1330-20-7, Ethylbenzene 100-41-4, Acetone 67-64-1, Propane 74-98-6, and Isobutane 75-28-5. This product is extremely flammable and should be kept away from all sources of ignition. Do not puncture, incinerate, or store container above 120 F. Exposure to high temperature may cause bursting. Do not place in direct sunlight or other heat sources. This product contains chemicals known to the State of California to cause cancer, birth defects and other reproductive harm. Overexposure to vapor may cause irritation to the nose and throat and may also cause dizziness, drowsiness and other central nervous system effects. Deliberate misuse by concentrating and inhaling the contents can be harmful or fatal. Inhalation of the mist may cause irritation to the respiratory tract and irregular heartbeats. **FIRST AID:** If exposed, wash eyes with water. If ingested may be harmful or fatal. Do not induce vomiting. For severe overexposure, call a physician immediately. For additional information consult the Material Safety Data Sheet for this product.

KEEP AWAY FROM CHILDREN

SPECIAL USAGE WARNINGS:

- Contents extremely flammable.
- Do not smoke while spraying.
- Extinguish all flames, pilot lights and heaters.
- Do not apply while equipment is energized.
- Vapors will accumulate readily and may ignite.
- Use only with adequate ventilation.
- Maintain ventilation during use and until vapors are gone.

© 2004 CRC Industries, Inc.,
Warminster, PA 18974

800-521-3168
(Technical Information)
800-272-4620
(Customer Service)
215-442-6260
(MSDS)

www.crcindustries.com

04A
Made in U.S.A.
CRC# 505A



Electronic

URETHANE SEAL COAT

Electronic & Electrical Insulator

Flexible, Non Conductive Polyurethane Film



No. 04060

Net Wt. 11 oz. (312 g)

DANGER: EXTREMELY FLAMMABLE.
HARMFUL OR FATAL IF SWALLOWED. VAPOR
HARMFUL. CONTENTS UNDER PRESSURE

Read warnings on back panel.