

Power Lube®

For complete product usage instructions and safety warnings in Spanish, go to www.crcindustries.com. Para obtener las instrucciones completas de uso y advertencias de seguridad del producto en Español, visite www.crcindustries.com.

Fast Acting – finds and stops squeaks. Penetrates deep through rust and scale – loosens frozen parts. **Lubricates and protects** metal surfaces without leaving a sticky residue. Seals out harmful moisture with a micro-thin continuous film – prevents the return of corrosion. **Concentrated** – clings to surfaces to deliver long lasting lubrication and protection. **Stops Binding** – makes assembly and disassembly easier. **Improves Electrical Properties** – displaces moisture, starts wet engines. Safe on most plastics.

MANY USES:

Hinges • Speedometer Cables • Seat Slides • Door Locks • Distributors • Power Antennas
Wheels • Lug Nuts • Battery Terminals • Air Tools • Switches • Computers • Clocks
Firearms • Fishing Reels • Bicycles and more

DIRECTIONS: Read entire label before using this product.

1. For personal safety, do not apply while equipment is energized.
2. Corrosion: Apply liberally and allow to penetrate for a few minutes. Tap part gently to set up vibration.
3. Lubrication: Spray in light, even coats to lubricate and protect metal surfaces.
4. Moisture: To displace moisture, spray wet surfaces until run-off is clear and moisture-free.

WARNING: Contains Petroleum Distillates 64742-47-8 & 64741-88-4, Butyl Stearate 123-95-5, Fatty Acid Ester 61791-48-8 and Carbon Dioxide 124-38-9. Do not puncture, incinerate or store can above 120°F. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Product is flammable and should be kept from all flames and other ignition sources. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. Overexposure to liquid or vapors can cause eye and skin irritation, irritation to upper respiratory tract, and central nervous system effects such as headache, dizziness, drowsiness or confusion. Deliberate misuse by concentrating and inhaling the contents can be harmful or fatal. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. Vapors are heavier than air and can accumulate in low areas. If you experience any symptoms listed on this label, increase ventilation or leave the area. Product may pose an aspiration hazard if swallowed.

FIRST AID: In case of eye or skin contact, flush with water for 15 minutes. If swallowed, DO NOT induce vomiting. If too much is breathed, remove to fresh air. For severe overexposure, call physician immediately. For additional information, consult SDS for this product.

DISPOSAL: All used and unused product should be disposed of in conformance with local, state and federal regulations. Do not dump in sewers, floor drains, on the ground, or into any body of water.

KEEP AWAY FROM CHILDREN

ELECTRICAL SHOCK HAZARD: This can will conduct electricity. Keep away from all live electrical sources including Battery Terminals, Solenoids, Electrical Panels and other electronic components. Do not use with the ignition in "ON" position. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

©2012 CRC Industries, Inc., Warminster, PA 18974
www.crcindustries.com
Made in USA 12A CRC#462E DOT 2Q

800-272-8963 Customer Svc
800-521-3168 Technical Info
215-442-6260 SDS



SCAN CODE
FOR MORE INFO



CRC

POWER LUBE®

Multi-Purpose Lubricant

LUBRICANTE MULTIUSO

Displaces Moisture • Frees Rusted Parts • Stops Squeaks



**DANGER: FLAMMABLE. HARMFUL OR FATAL
IF SWALLOWED. CONTENTS UNDER PRESSURE.**
READ WARNINGS ON BACK PANEL.

Net Wt. 9 oz. (255 g) No. 05005