

CRC® FREEZE-OFF®

CRC Freeze-Off® is a unique VOC-compliant formula that uses FREEZE SHOCK ACTION to Freeze, Penetrate & Loosen. Upon contact, this super penetrant immediately drops the temperature of the area in direct contact with the spray. The "freezing" effect cracks the rusted surfaces allowing **CRC Freeze-Off®** high purity penetrating solvent to reach deeper and work more effectively than other penetrants to loosen seized connections.

CRC Freeze-Off® Super Penetrant loosens rusted and corroded nuts, bolts, couplings, fittings, hinges, locks & frozen components. Specially formulated to dissolve rust gums & corrosion. Lubricating film prevents corrosion and displaces water. Use on automobiles, boats & watersports equipment, household items, plumbing fixtures, agricultural equipment and sporting goods.

DIRECTIONS: Read entire label before use. Follow all directions. 1. Spray directly on corroded fasteners from a short distance using straw attachment for at least 10-20 seconds. Maximum chilling effect will take place the longer the product is sprayed. 2. Allow penetrant to seep between joints and surface area for at least 1-2 minutes. 3. Tap joints lightly to speed progress. 4. Loosen or remove fastener. 5. If necessary, repeat steps 1-3 until fastener breaks free. 6. Severely frozen or welded fasteners may require the help of a power tool or nut cracker to loosen. 7. Do not apply while equipment is energized.

WARNING: Contains COzol® 306 Proprietary Blend, Aliphatic hydrocarbon 8052-41-3, Hydrotreated petroleum distillates 64742-47-8 and 64742-46-7, Turpentine oil 8006-64-2, 2-Butoxyethanol 111-76-2, Diacetone alcohol 123-42-2 and 1,1-Difluoroethane (HFC-152a) 75-37-6. Do not puncture, incinerate or store can above 120°F. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Product is extremely flammable; keep away from flames and other ignition sources. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Overexposure to vapor or liquid may cause irritation to the eye, nose, throat and skin and may cause headaches, dizziness, drowsiness and other central nervous system effects. Deliberate misuse by concentrating and inhaling the contents can be harmful or fatal. Inhalation of the mist may cause irritation of the respiratory tract and breathing problems. For additional information, consult the Material Safety Data Sheet for this product. **FIRST AID:** In case of eye or skin contact, flush with water for 15 minutes. If swallowed, may be harmful or fatal. DO NOT induce vomiting. If too much is breathed, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. For severe overexposure call a physician immediately. **DISPOSAL:** All used and unused product should be disposed of in accordance with local, state and federal regulations. DO NOT dump in sewers, floor drains, on the ground, or into any body of water. **KEEP AWAY FROM CHILDREN.**

SPECIAL USAGE WARNINGS: Contents Extremely Flammable. • Do not smoke while spraying. • Extinguish all flames, pilot lights, and heaters. • Do not apply while equipment is energized. • Vapors will accumulate readily and may ignite. • Use only with adequate ventilation; maintain ventilation during use and until vapors are gone.

©2007 CRC Industries, Inc.
Warminster, PA 18974
800-521-3168 (Technical Information)
800-272-9963 (Customer Service)

ELECTRICAL SHOCK HAZARD: This can will conduct electricity. Keep away from all live electrical sources including Battery Terminals, Solenoids, Electrical Panels and other electronic components. DO NOT use with ignition in "ON" position. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

215-442-6260 (MSDS)
www.crcindustries.com
CRC4447B 07A
Made in U.S.A.



FREEZE-OFF®

Super Penetrant



Remove
Seized Parts
FAST!

Freezes & Cracks Rust
Loosens Nuts, Bolts, Locks,
Assemblies and Hinges

DANGER: EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. EYE IRRITANT. CONTENTS UNDER PRESSURE. Read warnings on back panel.
Net Wt. 2 oz. (57g) No. 05010