

Chain Lube

For complete product usage instructions and safety warnings in Spanish, go to www.crcindustries.com. Para obtener las instrucciones completas de uso y advertencias de seguridad del producto en Español, visite www.crcindustries.com.

CRC Chain Lube is an advanced, high-performance, synthetic lubricant providing excellent protection for chains, open gears and exposed metal surfaces subject to severe loading. Sprays on like a liquid to penetrate deep, sets up like a grease for outstanding load-bearing protection.

- Safe on O-rings, X-rings and Z-rings • Works excellent in wet conditions
- Won't fling off or wash out • Extends chain life • Low odor • Clean appearance

Use as a lubricant and corrosion inhibitor on all types of drive chains, open gears, hoists, winches, pulleys, fork lifts, rollers, garage doors, bushings, seals, O-rings, X-rings, Z-rings and wire ropes.

DIRECTIONS: *Read entire label before using this product.*

1. Do not apply while equipment is energized. **2.** Shake well before use. **3.** Spray upper edges of overlapping chain side plates for the length of the chain. Allow lubricant to set up before energizing equipment.

WARNING: Contains petroleum naphtha 64742-49-0, liquefied petroleum gas 68476-86-8, 2-methylpentane 107-83-5, petrolatum 8009-03-8, and n-hexane 110-54-3. This product is extremely flammable and should be kept away from all sources of ignition. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F/49°C. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. Overexposure to liquid or vapors can cause eye and skin irritation, irritation to upper respiratory tract, and central nervous system effects such as headache, dizziness, drowsiness or confusion. Product may pose an aspiration hazard if swallowed. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. Vapors are heavier than air and can accumulate in low areas. If you experience any symptoms listed on this label, increase ventilation or leave the area.

SPECIAL USAGE WARNINGS: Contents Extremely Flammable. Do not smoke while spraying. Extinguish all flames, pilot lights, and heaters. Do not use on energized equipment. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until vapors are gone.

FIRST AID: In case of eye or skin contact, flush with water for 15 minutes. If too much is breathed, remove to fresh air. If breathing is difficult, give oxygen. If swallowed, DO NOT induce vomiting. Call a physician immediately. For additional information, consult SDS for this product.

DISPOSAL: All used and unused product should be disposed of in conformance with applicable regulations. Do not dump in sewers, on the ground, or into any body of water.

KEEP AWAY FROM CHILDREN

ELECTRICAL SHOCK HAZARD: This can will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. DO NOT use with ignition in "ON" position. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

Not for use in California.

©2014 CRC Industries, Inc., Warminster, PA 18974
www.crcindustries.com
Made in U.S.A. 14A CRC# 932A/B

800-521-3168 (Technical Information)
800-272-8963 (Customer Service)
215-442-6260 (SDS)




Chain Lube

Extends Chain Life, Clean & Fling-Proof

LUBRICANTE DE CADENAS



Penetrates Deep & Sets Up Like Grease



DANGER: EXTREMELY FLAMMABLE.
HARMFUL OR FATAL IF SWALLOWED. CAUSES
EYE IRRITATION. CONTENTS UNDER PRESSURE.
READ WARNINGS ON BACK PANEL.

Net Wt. 10 oz. (284 g) No. 05012

