

# CRC Gasket Remover

CRC Gasket Remover effectively removes and loosens gaskets, adhesives, sealants, cements and paints. Penetrating action loosens gasket material in minutes. Eliminates excessive scraping that could cause damage to gasket surfaces and flanges.

**DIRECTIONS:** Read entire label before using this product.

1. Always wear eye and hand protection when using this product. 2. Protect painted and finished surfaces from overspray. 3. For gasket and adhesive removal, liberally apply CRC Gasket Remover on gasket surface and let penetrate for 5 to 10 minutes. Use a gasket scraper to remove old gasket and a dry rag to remove adhesive. 4. For paint removal, liberally apply CRC Gasket Remover to painted surface. Allow to dry and remove paint with bristled brush. Do not apply to energized equipment.

*For the best sealing results, thoroughly clean gasket surface and use K&W Copper Coat gasket adhesive for a leak-proof seal.*

**WARNING:** Contains Acetone 67-64-1, N-methylpyrrolidone 872-50-4, Xylene 1330-20-7, Ethylbenzene 100-41-4, Liquefied petroleum gas 68476-86-8. Do not puncture, incinerate or store can above 120°F. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Keep away from flames and other ignition sources. This product contains chemicals known to the State of California to cause cancer, birth defects and other reproductive harm. Harmful if inhaled. Overexposure to vapors can cause eye and skin irritation, headaches, nausea, dizziness, irritation to upper respiratory tract and irregular heartbeats. Deliberate misuse by concentrating and inhaling the contents can be harmful or fatal. Use only in a well ventilated area. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. Insure good ventilation (for example opening windows and doors or operating an explosion proof fan) during use and afterwards to provide sufficient air to breathe and promote dissipation of product vapors. Vapors are heavier than air and can collect in low areas. If ventilation is not adequate, respiratory protection should be used. **FIRST AID:** In case of eye and skin contact flush with water for 15 minutes. If swallowed DO NOT induce vomiting. If too much is breathed remove to fresh air. For severe overexposure call physician immediately. For additional information consult the Material Safety Data Sheet for this product.

**KEEP AWAY FROM CHILDREN.**

**SPECIAL USAGE WARNINGS:** Contents Flammable. Do not smoke while spraying. Extinguish all flames, pilot lights and heaters. Do not apply while equipment is energized. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone.

**ELECTRICAL SHOCK HAZARD:** This can will conduct electricity. Keep away from all live electrical sources including Battery Terminals, Solenoids, Electrical Panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

**DISPOSAL:** All used and unused product should be disposed of in accordance with local, state and federal regulations. DO NOT dump in sewers, floor drains, on the ground or into any body of water.

VOC Category: Gasket Adhesive Remover  
VOC Limit: 50%

©2006 CRC Industries, Inc.  
Warminster, PA 18974  
800-521-3168 (Technical Information)  
800-272-8963 (Customer Service)

Made in U.S.A.  
CRC#553B 06A  
[www.crcindustries.com](http://www.crcindustries.com)  
215-442-6260 (MSDS)



# Technician Grade Gasket Remover

Removedor de juntas  
Fast-Acting Formula

Easily Removes Gaskets & Sealants  
Eliminates Excessive Scraping & Cleaning  
Also Removes Graffiti, Paint & Decals

**WARNING:** FLAMMABLE. HARMFUL IF INHALED OR SWALLOWED. EYE IRRITANT. CONTENTS UNDER PRESSURE. Read warnings on back panel.

Net Wt. 12 oz. (340 g) No. 05021