

# CRC Battery Terminal Protector

For complete product usage instructions and safety warnings in Spanish, go to [www.crcindustries.com](http://www.crcindustries.com). Para obtener las instrucciones completas de uso y advertencias de seguridad del producto en Español, visite [www.crcindustries.com](http://www.crcindustries.com).

This lead-free protective coating formula is specifically designed to protect battery terminals from corrosion, which is a major cause of hard starting and battery failure.

**DIRECTIONS:** Read entire label before using this product. Apply after battery has been connected.

1. Shake can well before using. 2. Clean away existing corrosion with CRC® Battery Cleaner, item #05023. 3. Apply an even coat to freshly cleaned hold-downs, bolts, brackets and terminals. 4. For preventive maintenance, reapply when red film turns clear. 5. When finished spraying, clean valve by turning can upside down and depressing actuator until only propellant escapes.

**WARNING:** Contains Hexane isomers 64742-49-0 / 107-83-5, Hydrocarbon propellant 68476-86-8, Stoddard solvent 8052-41-3, Heptane 142-82-5, Petroleum distillates 64741-88-4, Xylene 1330-20-7, and Ethylbenzene 100-41-4. Do not puncture, incinerate or store can above 120°F. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Contents are extremely flammable. Do not use near open flame or other sources of ignition. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. Overexposure to liquid or vapors can irritate eyes, skin and upper respiratory tract, and may cause headache, dizziness, drowsiness, or confusion. Deliberate misuse by concentrating and inhaling the contents can be harmful or fatal. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. Vapors are heavier than air and can accumulate in low areas. If you experience any symptoms listed on this label, increase ventilation or leave the area. Product may pose an aspiration hazard if swallowed. This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

**SPECIAL USAGE WARNINGS:** Contents Extremely Flammable. Do not smoke while spraying. Extinguish all flames, pilot lights, and heaters. Do not use on energized equipment. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until vapors are gone.

**FIRST AID:** In case of eye or skin contact, flush with water for 15 minutes. If swallowed, DO NOT induce vomiting. If too much is breathed, remove to fresh air. For severe overexposure, call a physician immediately. For additional information, consult the Material Safety Data Sheet for this product.

**DISPOSAL:** All used and unused product should be disposed of in conformance with local, state and federal regulations. Do not dump in sewers, on the ground, or into any body of water.

**KEEP AWAY FROM CHILDREN**

**ELECTRICAL SHOCK HAZARD:** This can will conduct electricity. Keep away from all live electrical sources including Battery Terminals, Solenoids, Electrical Panels and other electronic components. DO NOT use with ignition in "ON" position. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

©2009 CRC Industries, Inc., Warminster, PA 18974  
[www.crcindustries.com](http://www.crcindustries.com)  
Made in U.S.A. CRC#597N 09A DOT 2P

800-521-3168 (Technical Information)  
800-272-8963 (Customer Service)  
215-442-6260 (MSDS)



TECHNICIAN GRADE

# Battery Terminal Protector

**Prevents Corrosion**

Protector de terminales de  
batería profesional

**Prolongs Battery Life  
Assures Easier Starting**

**DANGER: EXTREMELY FLAMMABLE. HARMFUL  
OR FATAL IF SWALLOWED CONTENTS UNDER  
PRESSURE. READ WARNINGS ON BACK PANEL.**

**Net Wt. 7.5 oz. (213 g) No. 05046**