



Zinc-It®

Instant Cold Galvanize

Actively Fights Corrosion

**GALVANIZADOR
FRÍO INSTANTÁNEO**

Stops Rust • Dries Fast



DANGER: EXTREMELY FLAMMABLE.
HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL.
CAUSES SKIN IRRITATION. CONTENTS UNDER PRESSURE.
READ WARNINGS ON BACK PANEL.

Net Wt. 13 oz (368 g) No. 05048

Zinc-It® Instant Cold Galvanize

Para obtener información adicional en Español, visite www.crcindustries.com.

Galvanized protection fights rust and corrosion with >92% pure zinc. Provides the protection of expensive hot dip galvanizing.

- Protects iron and steel through sacrificial action. Protects even when scratched or abraded.
- Protects welds or bare metals on previously galvanized surfaces.
- Use as touch up for marred galvanized surfaces.

DIRECTIONS: *Read entire label before using this product.*

1. Prepare surface by removing all paint, loose rust, scale, oil and grease. Surface must be bare metal clean and dry. Mask area not to be sprayed. 2. Shake well until agitator ball is free. Repeat while using. 3. Best results are obtained when sprayed above 60°F. Hold can 8-12 inches from surface. Apply in light, even coats. 4. When finished spraying, clean valve by turning can upside down and pressing button. If clogging occurs, remove button, clean slot and orifice with fine wire and replace carefully. Important: Some paints are not compatible with either cold or hot dipped galvanized surfaces. Check paint for compatibility.

WARNING: Contains elemental zinc 7440-66-6, propane 74-98-6, toluene 108-88-3, n-butane 106-97-8, stoddard solvent 8052-41-3, isopropyl alcohol 67-63-0, aluminum sodium salt silicic acid 1344-00-9, zinc oxide 1314-13-2, and n-methyl-2-pyrrolidone 872-50-4. Contents extremely flammable. Do not smoke while spraying. Extinguish all flames, pilot lights and heaters. Keep away from heat/sparks/hot surfaces. Do not spray on an open flame or other ignition source or while equipment is energized. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F/49°C. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Avoid contact with skin and eyes. Do not breathe gas, mist or vapor. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. Overexposure to can cause skin irritation and headache, dizziness, drowsiness, or nausea. Product may pose an aspiration hazard if swallowed. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area.

FIRST AID: If swallowed, call your poison control center at 1-800-222-1222. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.

DISPOSAL: All used and unused product should be disposed of in conformance with applicable regulations. Do not dump in sewers, on the ground, or into any body of water.

KEEP AWAY FROM CHILDREN

ELECTRICAL SHOCK HAZARD: This metal can will conduct electricity. Keep away from all live electrical sources. Failure to observe this warning may result in serious injury and/or flash fire.



WARNING: This product can expose you to chemicals including toluene which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

VOC Category: Metallic Coating | MIR Limit: 1.90 (EPA) 1.25 (CA)

©2016 CRC Industries, Inc., Warminster, PA 18974
www.crcindustries.com
Made in U.S.A. 16A

800-521-3168 (Technical Information)
800-272-8963 (Customer Care)
215-442-6260 (SDS)

