

# CRC® De-Squeak™ BRAKE CONDITIONING TREATMENT

For complete product usage instructions and safety warnings in Spanish, go to [www.crcindustries.com](http://www.crcindustries.com). Para obtener las instrucciones completas de uso y advertencias de seguridad del producto en Español, visite [www.crcindustries.com](http://www.crcindustries.com).

**CRC DE-SQUEAK prevents brake noises before they occur. Metallic formula fills grooves and imperfections in the friction surfaces that commonly cause squeaks & squeals.**

**DIRECTIONS FOR USE:** Read entire label before using this product.

1. Using CRC's Brakleen®, thoroughly clean rotors and/or drums before applying conditioning treatment. 2. Shake can well before using. 3. Spray a light, even coat of DE-SQUEAK on all friction surfaces. If using on disc brakes, make sure DE-SQUEAK is applied to both sides of the rotors. 4. After reassembling the brake unit, drive the vehicle at a slow speed and apply the brakes 5 to 8 times. This will properly burnish DE-SQUEAK's metal particles into the friction surfaces.

Look for other quality brake products from CRC & STA-LUBE:

- Brakleen®
- Power Lube®
- Synthetic Brake & Caliper Grease
- Disc Brake Quiet
- Ultra Screwloose®
- Wheel Bearing Grease

**WARNING:** Contains Mineral Spirits 64742-88-7, Paraffin Oil 64742-62-7, Amorphous Silica 7631-86-9, Propane 74-98-6, and Butane 106-97-8. Do not puncture, incinerate or store can above 120°F. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Product is extremely flammable and should be kept from flames and other sources of ignition. Deliberate misuse by concentrating and inhaling the contents can be harmful or fatal. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. Vapors are heavier than air and can collect in low areas. If ventilation is not adequate, respiratory protection should be used.

**FIRST AID:** In case of eye and skin contact flush with water for 15 minutes. If swallowed, may be harmful or fatal. DO NOT induce vomiting. If too much is breathed remove to fresh air. For severe overexposure call physician immediately. For additional information consult the Material Safety Data Sheet for this product. **KEEP AWAY FROM CHILDREN.**

**SPECIAL USAGE WARNINGS:** Contents Flammable. Do not smoke while spraying. Extinguish all flames, pilot lights and heaters. Do not apply while equipment is energized. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone.


**ELECTRICAL SHOCK HAZARD:** This can will conduct electricity. Keep away from all live electrical sources including Battery Terminals, Solenoids, Electrical Panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

**DISPOSAL:** All used and unused product should be disposed of in accordance with local, state and federal regulations. DO NOT dump in sewers, floor drains, on the ground or into any body of water.

©2009 CRC Industries, Inc. • Warminster, PA 18974  
800-521-3168 (Technical Information) • 800-272-8963 (Customer Service)  
215-442-6260 (MSDS) • [www.crcindustries.com](http://www.crcindustries.com)

Made in U.S.A.  
09A

## USE ON EVERY BRAKE JOB!



# DE-SQUEAK™

CONDITIONING TREATMENT

*for Brakes*

**PREVENTS BRAKE NOISE**

**FOR USE ON DISC, DRUM & ABS SYSTEMS**

**DANGER:** EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. EYE IRRITANT. CONTENTS UNDER PRESSURE. Read warnings on back panel.

Net Wt. 2 oz. (56.7 g)

No. 05070



0 178254 05070 6