


Read entire label before
using this product.



BRÄKLEEN® Brake Parts Cleaner

■ NON-CHLORINATED

Part No. 05087



NET WEIGHT 355 lbs. (161 kg)



DANGER

Highly flammable liquid and vapor. Toxic if swallowed. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of damaging fertility. Suspected of damaging the unborn child. Causes damage to organs (eyes). May cause damage to organs through prolonged or repeated exposure (liver, kidneys, lungs, brain).

PRECAUTIONARY STATEMENTS

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Do not breathe mist or vapor. When exposed to extreme heat or hot surfaces, vapors may decompose to harmful or fatal corrosive gases such as formaldehyde. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national regulations.

| | | | |
|---------------------|-----------|----------------------------|----------|
| HEALTH | 3* | REACTIVITY | 0 |
| FLAMMABILITY | 3 | PERSONAL PROTECTION | B |

HAZARD: MINIMAL=0 SEVERE=4

©2014 CRC Industries, Inc.
Warminster, PA 18974
800-521-3168 (Technical Information)
800-272-8963 (Customer Service)
215-442-6260 (SDS)
www.crcindustries.com
14A CRC#483A Made in U.S.A.
FOR EMERGENCIES CALL CHEMTREC
1-800-424-9300

DATE CODE:
BATCH#:



- Removes Brake Fluid, Grease and Oil
- Degreases Instantly
- Leaves No Residue
- Contains No Chlorinated Solvents

Contains Methanol (67-56-1), Acetone (67-64-1), Toluene (108-88-3), 3-Methylhexane (589-34-4), n-Heptane (142-82-5), Methylcyclohexane (108-87-2), Cyclohexane (110-82-7), Ethylbenzene (100-41-4) and n-Hexane (110-54-3).

FIRST AID

If swallowed: Immediately call a poison center/doctor. Rinse mouth. Do NOT induce vomiting. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If exposed or concerned: Get medical attention. In case of fire: Do not use water jet as an extinguisher, as this will spread the fire.

This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product. Do not store container above 100 °F.

DIRECTIONS: 1. DO NOT use on polycarbonate plastics such as LEXAN®. If in doubt, call the manufacturer of the equipment. MAY ALSO BE HARMFUL TO OTHER PLASTICS. 2. Protect all rubber brake parts, plastic and painted surfaces from product and overspray. DO NOT spray directly on painted surfaces. DO NOT apply while equipment is energized. 3. Wet down surfaces to be cleaned. Avoid breathing any dust or vapors that may become airborne. 4. After all surfaces have been wetted, continue using BRAKLEEN to remove contaminants. 5. Air dry or wipe with a clean cloth. 6. For heavy deposits, repeat application as necessary. 7. Runoff should be collected and disposed of properly.

Not for use in California. See SDS for additional state sales restrictions.