CRC MAF Sensor Cleaner

For complete product usage instructions and safety warnings in Spanish, go to www.crcindustries.com. Para obtener las instrucciones completas de uso y advertencias de seguridad del producto en Español, visite www.crcindustries.com.

Most fuel injected vehicles are equipped with a mass air flow (MAF) sensor to measure air velocity which the computer uses to determine the proper air/fuel mixture. However, the MAF sensor gets dirty with debris, oil, air filter fibers, dust and pollen causing inaccurate measurements of intake air flow which results in a "rich" running engine, loss of power and excess emissions.

• Plastic Safe • Safe on Sensitive Equipment • Increases Horsepower
• Reduces Rough Idle • Decreases Hesitation and Pinging • Improves Fuel Economy & MPG
• Entire Job Takes Less than 10 Minutes!

Don't use aggressive chemicals like brake cleaner, carburetor cleaner or air intake cleaner on MAF sensors. These can cause serious damage to sensitive parts. Use CRC MAF SENSOR CLEANER – the right product for the job!

FOR ALL GAS AND DIESEL VEHICLES EQUIPPED WITH MAF SENSORS

DIRECTIONS: ***Read entire label before using this product.***
1. Do not apply while equipment is energized. Turn off vehicle. 2. Locate your MAF between the air box and throttle body. **3.** Unplug MAF wire harness. **4.** Remove MAF housing. (Typically a screwdriver will work, you may need a T-20 TORX® Security bit.) **5.** Place shop towel under MAF to catch any run-off. **6.** With straw attached, apply 10-15 sprays of CRC MAF SENSOR CLEANER onto hot-wires or hot plate. DO NOT contact hot-wires with straw or any other object. **7.** Be sure to spray all sides of the MAF sensor and clean all wires and connectors. **8.** Reassemble MAF and allow to dry thoroughly before reactivating. **9.** For best results clean your mass air flow sensor every time you clean or change your air filter. **10.** DO NOT use on vehicles with a Karman-Vortex air flow sensor, e.g. Toyota Supra Turbos, Mitsubishi's and most Lexus vehicles.

QUICK DRYING FORMULA. SAFE TO USE ON MOST SENSORS & CONNECTORS!
FEATURING ADVANCED COzol® TECHNOLOGY

** Test data obtained on a dynamometer at **R/T Tuning in Lansdale, PA**.*

WARNING: Contains Hexane isomers 64742-49-0 / 107-83-5, COzol® 204 proprietary blend, Carbon dioxide 124-38-9, and n-Hexane 110-54-3. Do not puncture, incinerate or store can above 120ºF. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Product is extremely flammable and should be kept from all flames and other ignition sources. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. Overexposure to liquid or vapors can cause eye and skin irritation, irritation to upper respiratory tract, and central nervous system effects such as headache, dizziness, drowsiness or confusion. Product may pose an aspiration hazard if swallowed. Deliberate misuse by concentrating and inhaling the contents can be harmful or fatal. This product contains chemicals known to the State of California to cause birth defects or other reproductive harm. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. Vapors are heavier than air and can accumulate in low areas. If ventilation is not adequate or you experience any symptoms listed on this label, increase ventilation, use respiratory protection or leave the area. **FIRST AID:** In case of eye or skin contact, flush with water for 15 minutes. If swallowed, DO NOT induce vomiting. If too much is breathed, remove to fresh air. For severe overexposure, call physician immediately. For additional information, consult SDS for this product. **DISPOSAL:** All used and unused product should be disposed of in conformance with local, state and federal regulations. Do not dump in sewers, on the ground, or into any body of water. **KEEP AWAY FROM CHILDREN**

SPECIAL USAGE WARNINGS: Contents Extremely Flammable. Do not smoke while spraying. Extinguish all flames, pilot lights, and heaters. Do not use on energized equipment. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until vapors are gone.

ELECTRICAL SHOCK HAZARD: This can will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. DO NOT use with ignition in "ON" position. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

©2013 CRC Industries, Inc., Warminster, PA 18974
www.crcindustries.com
800-521-3168 (Technical Information)
800-272-8963 (Customer Service)
215-442-6260 (SDS)
Made in U.S.A. CRC#599C 13A DOT 2Q

FLAMMABLE

0 78254 05110 9

CRC

Mass Air Flow Sensor Cleaner

Limpiador del sensor de flujo de aire



PROVEN to Gain 4-10 Horsepower at the Wheels!*

Evaporates in seconds!

Use every time you clean or change the air filter!

- ***Safely Cleans & Protects Mass Air Flow Sensors***
- ***Plastic Safe & Leaves No Residue***
- ***Improves Air/Fuel Ratio and Increases MPG***

SCAN CODE FOR MORE INFO

DANGER: EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. CONTENTS UNDER PRESSURE.
READ WARNINGS ON BACK PANEL.

Net Wt. 11 oz. (312 g) **No. 05110**