

WARNING: Contains dimethyl siloxanes and silicones 63148-62-9, silicon dioxide amorphous 112945-52-5, polytetrafluoroethylene 9002-84-0 and nitrogen 7727-37-9. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F/49°C. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. When exposed to extreme heat or hot surfaces, vapors may decompose to harmful or fatal corrosive gases such as hydrogen fluoride. Avoid contact with eyes. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. **FIRST AID:** In case of eye or skin contact, flush with water for 15 minutes. If swallowed, contact a poison control center. For additional information, consult SDS for this product. **DISPOSAL:** All used and unused product should be disposed of in conformance with local, state and federal regulations. Do NOT dump in sewers, floor drains, on the ground or into any body of water.

KEEP AWAY FROM CHILDREN

ELECTRICAL SHOCK HAZARD:

This can will conduct electricity. Do not touch can to live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from electrical shock.

CRC

**TECHNICIAN GRADE
Dielectric Grease**

Seals • Lubricates • Protects • Insulates

GRASA DIELECTRICA

Waterproofs Electrical Contacts



**Unique Precision
Applicator for
Maximum Control**

- No Waste
- No Mess

WARNING: CONTENTS UNDER PRESSURE.
READ WARNINGS ON BACK PANEL.

Net Wt. 3.3 oz (93 g) No. 05113



**Technician Grade
Dielectric Grease**

For complete product usage instructions and safety warnings in Spanish, go to www.crcindustries.com. Para obtener las instrucciones completas de uso y advertencias de seguridad del producto en Español, visite www.crcindustries.com.

SEALS, LUBRICATES, PROTECTS and INSULATES electrical contacts, spark plugs, battery terminals and fasteners from moisture. LUBRICATES and SEALS rubber and plastic parts – including O-rings. WATERPROOFS electrical contacts and components to protect against arcing due to moisture and other contaminants. IMPROVES electrical performance during adverse conditions such as rain, fog, salt spray and temperature extremes. UNIQUE PRECISION APPLICATOR for maximum control, perfect beads, no waste and no mess.

DIRECTIONS: Read entire label before using this product.

1. For personal safety, do not apply while equipment is energized.
2. Shut off power supply, be sure all stored power is drained from system and allow hot surfaces to cool before using this product.
3. Clean surfaces, connectors and contacts with CRC QD Electronic Cleaner, part #05103.
4. Remove cap, pull tab, then adjust cap following min/max arrow to control grease width. Press handle to apply.
5. Squeeze trigger to dispense product. Coat areas requiring lubrication or protection.



©2016 CRC Industries, Inc., Warminster, PA 18974
800-272-8963 Customer Care 16A
800-521-3168 Technical Info Made in USA
215-442-6260 SDS www.crcindustries.com