




# Ultra Low VOC

## Brakleen®

### Brake Parts Cleaner



**NON-CHLORINATED • ULTRA LOW VOC**  
**Complies with SCAQMD Rule 1171**

**Removes Brake Fluid, Grease and Oil**  
**Degreases Instantly • Leaves No Residue**  
**Contains No Chlorinated Solvents**

**DANGER: EXTREMELY FLAMMABLE.**

**EYE AND SKIN IRRITANT.**

Read warnings on back panel.

No. 05152

Net Contents:

1 gal. (3.78L)



## CRC Ultra Low VOC Brakleen® Non-Chlorinated

**CRC ULTRA LOW VOC BRAKLEEN Non-Chlorinated** removes brake fluid, grease, oil and other contaminants from brake linings and drums. It also stops disc brake squeal and can be applied without disassembling the brake unit.

Does not contain Chlorinated Solvents or Silicones.

#### APPLICATIONS:

**BRAKE LININGS • SPRINGS • CYLINDERS • DRUMS**  
**CLUTCHES • C.V. JOINTS • DISC BRAKE PARTS**  
**RELATED BRAKE PARTS**

**DIRECTIONS:** *Read entire label before using this product.* NOT FOR USE ON SENSITIVE ELECTRONIC EQUIPMENT SUCH AS TAPE DECKS, VCRS, COMPUTERS, ETC. USE CRC QD ELECTRONIC CLEANER FOR THESE APPLICATIONS.

1. Do NOT use on polycarbonate plastics such as LEXAN®. If in doubt call the manufacturer of the equipment. **MAY ALSO BE HARMFUL TO OTHER PLASTICS.**

**WARNING:** Contains Toluene 108-88-3 and Acetone 67-64-1. This product contains chemicals known to the State of California to cause cancer, birth defects and other reproductive harm. Overexposure to vapors may cause eye and skin irritation, headaches, nausea, dizziness, irritation to upper respiratory tract and irregular heartbeats. Product is extremely flammable. Keep away from flames and other ignition sources. Deliberate misuse by concentrating and inhaling the contents can be harmful or fatal. Use only in a well ventilated area. Avoid continuous breathing of vapor and spray mist. **Excessive inhalation of dust and/or vapors may be harmful.** Avoid contact with skin and eyes. Vapors are heavier than air and will collect in low areas. If ventilation is not adequate, respiratory protection should be used.

**FIRST AID:** In case of eye or skin contact, flush with water for 15 minutes. If swallowed, do not induce vomiting. If too much is breathed, remove to fresh air. For severe overexposure, call a physician immediately.

**HANDLING AND SPILL PRECAUTIONS:** Keep container closed. Wash thoroughly after handling. Do not enter where vapors are suspected in high concentrations unless air-supplied positive pressure breathing apparatus is used and a trained observer is present and equipped with rescue gear. Vapors of this solvent may develop a flammable atmosphere in contact with flames, high energy sparks or high intensity sources of heat. Do not cut or weld containers due to explosion hazard. FOR SPILLS: use proper

2. Protect all rubber brake parts, plastic and painted surfaces from product and overspray. DO NOT spray directly on painted surfaces. DO NOT apply while equipment is energized.

3. Wet down area to be cleaned with SCAQMD BRAKLEEN. Avoid breathing any dust or vapors that may become airborne. (See inhalation warning.)

4. After all surfaces have been wetted, continue applying Ultra Low VOC BRAKLEEN to remove contaminants.

5. Air dry or wipe with a clean cloth.

6. For heavy deposits, repeat application as necessary.

7. Runoff should be collected and disposed of properly. (See disposal statement.)

Professional users should consult MSDS and follow all applicable OSHA regulations.

protective equipment. Take precautions as necessary to prevent contamination of ground or surface waters. FOR SMALL SPILLS, use absorbent and sweep into closed containers for disposal. For large spills evacuate the area, dike and transfer into containers for disposal.

**DISPOSAL:** Unused contents and containers must be disposed of in accordance with all federal, state and local regulations. EMPTY containers may be offered to a qualified reconditioner. Unused contents may be offered to a licensed reclaimer. Do not dump in sewers, on the ground or into any body of water.

For additional information, consult the Material Safety Data Sheet for this product.

**KEEP AWAY FROM CHILDREN**

©2000 CRC Industries, Inc.  
Warminster, PA 18974  
800-521-3168 (Tech. Information)  
800-272-8963 (Customer Service)  
215-442-6260 (MSDS)  
www.crcindustries.com  
Made in U.S.A. CRC#68 00A

