

WARNING: Contains Toluene 108-88-3 and Acetone 67-64-1. Cannot be made non-poisonous. This product contains chemicals known to the State of California to cause cancer, birth defects and other reproductive harm. Overexposure to vapors may cause skin and eye irritation, headaches, nausea, dizziness, irritation to upper respiratory tract and irregular heartbeats. Deliberate misuse by concentrating and inhaling the contents may be harmful or fatal. **Excessive inhalation of dust and/or vapors may be harmful.** Product is extremely flammable. Keep away from flames and other ignition sources. Use only in a well ventilated area. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. Vapors are heavier than air and will collect in low areas, pits, small rooms, or other unventilated areas. If ventilation is not adequate, respiratory protection should be used.

FIRST AID: In case of eye or skin contact, flush with water for at least 15 minutes. If swallowed, do not induce vomiting. If too much is breathed, remove to fresh air. For severe overexposure, call a physician immediately.

HANDLING AND SPILL PRECAUTIONS: Keep container closed. Wash thoroughly after handling. Do not enter where vapors are suspected in high concentrations, unless air-supplied positive pressure breathing apparatus is used and a trained observer is present and equipped with rescue gear. Vapors of this solvent may develop an extremely flammable atmosphere in contact with flames, sparks, or other ignition sources. Do not cut or weld containers due to explosion hazard. **FOR SPILLS,** use proper protective equipment. Take precautions as necessary to prevent contamination of ground or surface water. For small spills, use absorbent and sweep into closed containers for disposal. For large spills, evacuate the area, dike and transfer into containers for disposal.

DISPOSAL: Unused contents and containers must be disposed of in accordance with all federal, state, and local regulations. EMPTY containers may be offered to a qualified reconditioner. Unused contents may be offered to a licensed reclaimer. Do not dump in sewers, on the ground or into any body of water.

For additional information, consult the Material Safety Data Sheet for this product.


SPECIAL USAGE WARNINGS:

- Contents Extremely Flammable.
- Do not smoke while spraying.
- Extinguish all flames, pilot lights and heaters.
- Do not apply while equipment is energized.
- Vapors will accumulate readily and may ignite.
- Use only with adequate ventilation; maintain ventilation during use and until vapors are gone.

KEEP AWAY FROM CHILDREN

CRC

Ultra Low VOC Brākleen® Brake Parts Cleaner



NON-CHLORINATED/ ULTRA LOW VOC
Complies with SCAQMD Rule 1171



Removes Brake Fluid, Grease and Oil
Degreases Instantly
Leaves No Residue
Contains No Chlorinated Solvents

NET WEIGHT:

33 lbs. (15 Kg)

Part No. 05153

DANGER: EXTREMELY FLAMMABLE.

EYE AND SKIN IRRITANT.

Read warnings on side panel.

CRC Ultra Low VOC Brākleen® removes brake fluid, grease, oil and other contaminants from brake linings and drums. It also stops disc brake squeal and can be applied without disassembling the brake unit.

Does not contain Chlorinated Solvents or Silicones.

APPLICATIONS:

- Brake Linings
- Drums
- Disc Brake Pads
- Cylinders
- Springs
- Other Related Brake Parts

DIRECTIONS:

Read entire label before using this product.

1. **DO NOT** use on polycarbonate plastics such as LEXAN®. If in doubt call the manufacturer of the equipment. **MAY ALSO BE HARMFUL TO OTHER PLASTICS.**
2. Protect all rubber brake parts, plastic and painted surfaces from product and overspray. **DO NOT** spray directly on painted surfaces. **DO NOT** apply while equipment is energized.
3. Wet down surfaces to be cleaned. Avoid breathing any dust or vapors that may become airborne. (See inhalation warning.)
4. After all surfaces have been wetted, continue spraying Ultra Low VOC BRAKLEEN® to remove contaminants.
5. Air dry or wipe with a clean cloth.
6. For heavy deposits, repeat application as necessary.
7. Runoff should be collected and disposed of properly. (See disposal statement.)

Professional users should consult MSDS and follow all applicable OSHA regulations.

**STORAGE OF THIS CONTAINER
OUTSIDE WILL CAUSE THIS LABEL
TO BECOME ILLEGIBLE.**

©2000 CRC Industries, Inc.
Warminster, PA 18974
800-521-3168 (Technical Information)
800-272-8963 (Customer Service)
215-442-6260 (MSDS)
www.crcindustries.com
Made in U.S.A. CRC#668 00A

