



*Diesel*<sup>TM</sup>

# Fuel Therapy<sup>®</sup>

## Diesel Injector Cleaner

*Limpiador para Inyectores de Diesel*

*Plus*

- *Provides Top-Tier Clean-Up with Max Treat*
- *Cleans Injectors and Prevents Corrosion*
- *Adds Lubricity to Low Sulfur Fuel*
- *Increases MPG*

**Treats  
500  
Gals.**

**DANGER:** COMBUSTIBLE.  
HARMFUL OR FATAL IF SWALLOWED.  
Read warnings on back panel.

Part No. 05228

Net Contents: 1 Gallon (3.78 L)



*Diesel™*

# FUEL THERAPY® Diesel Injector Cleaner Plus

For complete product usage instructions and safety warnings in Spanish, go to [www.crcindustries.com](http://www.crcindustries.com). Para obtener las instrucciones completas de uso y advertencias de seguridad del producto en Español, visite [www.crcindustries.com](http://www.crcindustries.com).

Emulsions reducing formula rated "SUPERIOR" in Cummins L-10 test for injector cleanliness. Exceeds CSCA requirements for Peugeot XUD-9 injector cleanliness.

- Cleans Injectors
- Lubricates Fuel
- Maintains Cetane Rating
- Stabilizes Fuel
- Increases MPG
- Increases Power
- Reduces Emissions
- Prevents Corrosion
- Reduces Black Smoke

This product complies with the federal ultra-low sulfur content requirements for use in all diesel motor vehicles and non-road engines.

CRC DIESEL Fuel Therapy® is non-corrosive and contains no alcohol. Compatible with all diesel fuels. OK for biodiesel.

**DIRECTIONS:** *Read entire label before using this product.*

**For preventive maintenance and biodiesel fuels:** This container is sufficient to treat up to 500 gallons of diesel fuel.

**For pre-existing conditions:** Use 1 gallon to each 200 gallons of fuel. Pour into fuel tank and operate normally.

For cold conditions, use CRC DIESEL FUEL THERAPY with Anti-Gel (#05428). For anticipated extreme conditions, add CRC DIESEL Cold Flow™ Anti-Gel with Lubricity (#05632) to fuel prior to temperature drop.

**WARNING:** Contains petroleum distillates 64742-80-9, 64742-54-7, and mineral spirits 8052-41-3. Product is combustible and should be kept from heat, open flames and other ignition sources. Do not store container above 100 °F. Avoid continuous breathing of vapor. Avoid contact with skin and eyes. Overexposure to liquid or vapors can cause irritation to eyes, skin, and upper respiratory tract, and central nervous system effects such as headache or dizziness. Product may pose an aspiration hazard if swallowed. Use with adequate ventilation. This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

**FIRST AID:** In case of eye or skin contact, flush with water for 15 minutes. If swallowed, DO NOT induce vomiting. If too much is breathed, remove to fresh air. For severe overexposure, call physician immediately. For additional information, consult SDS for this product.

**DISPOSAL:** All used and unused product should be disposed of in conformance with local, state and federal regulations. Do not dump in sewers, floor drains, on the ground, or into any body of water.

**KEEP AWAY FROM CHILDREN**

©2015 CRC Industries, Inc., Warminster, PA 18974

[www.crcindustries.com](http://www.crcindustries.com)

Made in the U.S.A. CRC#605Q 15A



800-521-3168 (Technical Information)

215-442-6260 (SDS)

800-272-8963 (Customer Care)

