



Inner Slide Lube

Extends Equipment Life

ACEITE PARA RIELES INTERNOS CRC®

CLINGS TO METAL SURFACES
PREVENTS CORROSION

Prevents Destructive Metal-to-Metal Contact



DANGER: EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. MAY IRRITATE SKIN. CONTENTS UNDER PRESSURE.
READ WARNINGS ON BACK PANEL.

Net Wt. 10.5 oz. (298 g) No. 05305



CRC Inner Slide Lube

For complete product usage instructions and safety warnings in Spanish, go to www.crcindustries.com. Para obtener las instrucciones completas de uso y advertencias de seguridad del producto en Español, visite www.crcindustries.com.

CRC Inner Slide Lube is specially formulated to adhere to fork lift inner slide rails providing long lasting smooth flawless operating over extended periods. CRC Inner Slide Lube is designed to lubricate, increase slide motion, and protect against rust and corrosion of fork lift inner slide rails.

DIRECTIONS: Read entire label before using this product.

1. Do not apply while equipment is energized.
2. Shake well before use.
3. Spray in generous even coats.
4. Completely cover fork lift inner slide rails.

WARNING: Contains Heptane 142-82-5, Naphthenic distillates 64742-65-0, liquefied petroleum gas 68476-85-7, molybdenum disulfide 1317-33-5 and antimony diamidithiocarbamate 15890-25-2. This product is extremely flammable and should be kept away from all sources of ignition. Do not puncture, incinerate or store container above 120°F. Exposure to high temperature may cause bursting. Do not place in direct sunlight or near other heat sources. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. Overexposure to liquid or vapors can cause eye and skin irritation, irritation to upper respiratory tract, and central nervous system effects such as headache, dizziness, drowsiness or confusion. Product may pose an aspiration hazard if swallowed. Deliberate misuse by concentrating and inhaling the contents can be harmful or fatal. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. Vapors are heavier than air and can accumulate in low areas. If you experience any symptoms listed on this label, increase ventilation or leave the area.

SPECIAL USAGE WARNINGS: Contents Extremely Flammable. Do not smoke while spraying. Extinguish all flames, pilot lights, and heaters. Do not use on energized equipment. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until vapors are gone.

FIRST AID: In case of eye or skin contact, flush with water for 15 minutes. If swallowed, DO NOT induce vomiting. If too much is breathed, remove to fresh air. If breathing is difficult, give oxygen. For severe overexposure, call a physician immediately. For additional information, consult MSDS for this product.

DISPOSAL: All used and unused product should be disposed of in conformance with local, state and federal regulations. Do not dump in sewers, on the ground, or into any body of water.

KEEP AWAY FROM CHILDREN

ELECTRICAL SHOCK HAZARD: This can will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. DO NOT use with ignition in "ON" position. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

©2011 CRC Industries, Inc., Warminster, PA 18974
800-272-8963 Customer Svc
800-521-3168 Technical Info
215-442-6260 MSDS

www.crcindustries.com
Made in USA
11A

DOT 2Q M5749 DSC

