

CRC

Top Engine Cleaner

ENGINE TUNE-UP & DECARBONIZER
AFINADOR Y DESCARBONIZADOR
DE MOTORES

**Combustion Chamber
& Induction System
Cleanup**

- Instantly Cleans Power-Robbing Carbon Deposits, Gums & Varnish
- Dramatically Improves Engine Performance & Power
- For all 2 & 4 Cycle Gasoline Engines

• **CARS** • **BOATS** • **BIKES**
• **TRUCKS** • **SMALL ENGINES**

DANGER: EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. EYE IRRITANT. CONTENTS UNDER PRESSURE. READ WARNINGS ON BACK PANEL.

Net Wt. 12 oz. (340 g)

No. 05312



SCAN CODE
FOR MORE INFO



CARS • BIKES
BOATS • ATVS
RVS • TRUCKS
TRACTORS



CRC Top Engine Cleaner

For complete product usage instructions and safety warnings in Spanish, go to www.crcindustries.com. Para obtener las instrucciones completas de uso y advertencias de seguridad del producto en Español, visite www.crcindustries.com.

Reduced engine performance, increased fuel consumption, rough idling and engine knocking, ping/ing or run-on are all signs of carbon build-up. Use CRC Top Engine Cleaner to dissolve carbon build-up and other harmful deposits from the intake system, valves and combustion chamber. Spray CRC Top Engine Cleaner directly into the throttle body, behind the throttle plate, using the attached extension tube.

- Dissolves gums, varnish & carbon deposits
- Helps increase MPG
- Eliminates pre-ignition (knock)
- Provides a smoother-running engine
- Improves compression
- Restores lost power and pickup
- Cures hesitation and stalling

DIRECTIONS: Read entire label before using this product.

1. Ensure vehicle is well ventilated. Exhaust will be extreme as internal motor is being cleaned. DO NOT treat vehicle in enclosed garage.
2. With vehicle in park, run engine until normal operating temperature is achieved. Idle engine.
3. Locate throttle body and insert extension tube about 2 inches past the throttle plate.
4. Increase engine idle to about 2,000 RPM and spray CRC Top Engine Cleaner directly into the throttle body until entire can is dispensed (about 2 to 3 mins.)
5. Turn engine off and allow to heat-soak for 15 - 20 minutes.
6. Restart engine and drive until white smoke is gone. For extreme build-up, repeat procedure.

WARNING: Contains Naphthenic oil 64742-52-5/64742-53-6, 2-butoxyethanol 111-76-2, aromatic hydrocarbons 64742-95-6/64742-94-5, diacetone alcohol 123-42-2, and hydrocarbon propellant 68476-86-8. Do not puncture, incinerate or store can above 120°F. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Contents are extremely flammable and should be kept away from open flames and other sources of ignition. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. Overexposure to liquid or vapors can cause moderate to severe eye irritation, skin irritation and dryness, irritation to upper respiratory tract, and central nervous system effects such as headache, dizziness, drowsiness or confusion. Product may pose an aspiration hazard or cause nausea if swallowed. Deliberate misuse by concentrating and inhaling the contents can be harmful or fatal. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. Vapors are heavier than air and can accumulate in low areas. If you experience any symptoms listed on this label, increase ventilation or leave the area.

SPECIAL USAGE WARNINGS: Contents Extremely Flammable. Do not smoke while spraying. Extinguish all flames, pilot lights, and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until vapors are gone.

FIRST AID: In case of eye or skin contact, flush with water for 15 minutes. If swallowed, DO NOT induce vomiting. If too much is breathed, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. For severe overexposure, call a physician immediately. For additional information, consult the Material Safety Data Sheet for this product.

DISPOSAL: All used and unused product should be disposed of in conformance with local, state and federal regulations. Do NOT dump in sewers, floor drains, on the ground or into any body of water.

KEEP AWAY FROM CHILDREN

ELECTRICAL SHOCK HAZARD: This can will conduct electricity. Keep away from all live electrical sources including Battery Terminals, Solenoids, Electrical Panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

Not for use in California

©2011 CRC Industries, Inc., Warminster, PA 18974

www.crcindustries.com

Made in USA CRC#0684 11A

800-272-8963 Customer Svc

800-521-3168 Technical Info

215-442-6260 MSDS



0 78254 05312 17