

# CRC

# Motor Treatment

INTERNAL ENGINE & CRANKCASE CLEANER  
TRATAMIENTO PARA EL MOTOR

## Carbon Clean-Out

GAS • DIESEL • OIL  
ETHANOL

- Instantly Cleans Power-Robbing Carbon Deposits, Gums & Varnish
- Cures Rough Idle, Hesitation & Pinging
- Fuel Stabilizer – Removes Moisture From Fuel & Oil



- CARS** • **BOATS** • **BIKES**
- TRUCKS** • **SMALL ENGINES**

**DANGER:** COMBUSTIBLE. HARMFUL OR FATAL IF SWALLOWED. READ WARNINGS ON BACK PANEL.

Net 16 fl. oz. (474 mL)

No. 05316

CARS • BIKES  
BOATS • ATVS  
RVs • TRUCKS  
TRACTORS



100% PURE  
PETROLEUM

## CRC Motor Treatment

For complete product usage instructions and safety warnings in Spanish, go to [www.crcindustries.com](http://www.crcindustries.com). Para obtener las instrucciones completas de uso y advertencias de seguridad del producto en Español, visite [www.crcindustries.com](http://www.crcindustries.com).

DIRECTIONS: Read entire label before using this product.

### ADD TO OIL

Over time, prolonged idle, stop & go driving, dirt, moisture and extreme operating temperatures can promote sludge build-up in motor oil causing power and performance loss.

CRC Motor Treatment liquefies built-up carbon, gum and varnish, cleans sticky valve lifters, piston rings and PCV systems slowly, while you drive, to prevent chunks of sludge from clogging oil flow.

1. Add 1 ½ fl. oz. of CRC Motor Treatment per quart of oil directly into crankcase. Compatible with all motor oils, including synthetic.
2. Drive vehicle for 30 to 60 miles, then perform oil change service, including new filter.
3. For prolonged cleaning, add 1 ½ fl. oz. to fresh oil. Change oil & filter when dirty.

### ADD TO FUEL

CRC Motor Treatment cleans fuel injectors, carburetor jets, intake valves & pistons, lubricates upper cylinders, cures hesitation and pings, restores power and pick-up, removes moisture and stabilizes fuel. **This product complies with the federal ultra-low sulfur content requirements for use in all diesel motor vehicles and non-road engines.**

1. Add 1 fl. oz. per gallon of gas or diesel directly into fuel tank. Drive as normal. Oxygen sensor safe.

### ADD TO COMBUSTION CHAMBER

For faster and more complete cleaning add CRC Motor Treatment directly into the combustion chamber.

1. Ensure vehicle is well ventilated. Exhaust will be extreme as internal motor is being cleaned. DO NOT treat vehicle in enclosed garage.
2. Run engine until normal operating temperature is achieved. Idle engine.
3. **IMPORTANT: Check with a certified technician** before inducing product into any vacuum lines to ensure they feed all cylinders evenly/safely. NOTE: Only a professional technician should treat Vortec or Subaru "H" style engines which do not have vacuum lines that distribute evenly.
4. Locate a main manifold vacuum line that distributes evenly to all cylinders.
5. SLOWLY add 5 to 8 fl. oz. of CRC Motor Treatment through the vacuum line. **DO NOT submerge the vacuum line** in the product. Allow the product to be "slurped" into the vacuum line slowly while maintaining RPM of 2,000.
6. Turn off ignition and let product heat-soak for 10 – 20 minutes.
7. Restart engine and drive until white smoke is gone.

### SMALL 2-CYCLE or 4-CYCLE ENGINES

Restores power, smooths rough idle, cleans injectors and carbon build-up, removes moisture and stabilizes fuel.

1. Add 2 fl. oz. per gallon of gas, or gas/oil mixture.

**WARNING:** Contains Paraffinic distillates 64742-54-7, Mineral spirits 8052-41-3, and 2-Butoxyethanol 111-76-2. Product is combustible and should be kept from heat, open flames and other ignition sources. Avoid continuous breathing of vapor. Avoid contact with skin and eyes. Overexposure to liquid or vapors can cause irritation to eyes, skin, and upper respiratory tract, and central nervous system effects such as headache or dizziness. Product may pose an aspiration hazard if swallowed. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. Vapors are heavier than air and can accumulate in low areas. If you experience any symptoms listed on this label, increase ventilation or leave the area. This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. **FIRST AID:** In case of eye or skin contact, flush with water for 15 minutes. If swallowed, DO NOT induce vomiting. If too much is breathed, remove to fresh air. For severe overexposure, call physician immediately. For additional information, consult MSDS for this product. **DISPOSAL:** All used and unused product should be disposed of in conformance with local, state and federal regulations. Do not dump in sewers, floor drains, on the ground, or into any body of water. **KEEP AWAY FROM CHILDREN**

©2011 CRC Industries, Inc., Warminster, PA 18974  
[www.crcindustries.com](http://www.crcindustries.com)  
Made in USA CRC#0864 11B DSC

800-272-8963 Customer Svc  
800-521-3168 Technical Info  
215-442-6260 MSDS

