GDI IVD® Intake Valve & Turbo Cleaner

For complete product usage instructions and safety warnings in Spanish, go to www.crcindustries.com. Para obtener las instrucciones completas de uso y advertencias de seguridad del producto en Español, visite www.crcindustries.com.

Deposits form in every fuel system but the amount and how quickly they form depends on the quality of fuel and oil you use, driving style and engine type. GDI engine intake valves are prone to rapid deposit buildup in as few as 5,000 to 10,000 miles. **SYMPTOMS** include hard starts, rough idle, poor acceleration, reduced MPG, excess emissions and power loss.

PATENT PENDING — FILED FOR U.S. PATENT — ALL RIGHTS RESERVED

Use Every 10,000 Miles or Before Every Oil Change

Highest Available PEA Detergency Dissolves Deposits • Increases Power & Torque Stabilizes Rough Idle • Alleviates Hesitation & Pinging • Eliminates Starting Problems Reduces Emissions • Improves Fuel Economy & MPG • Easy to Use!

DIRECTIONS: ***Read entire label before using this product.***
Professional Users: 1. Warm up engine. **2.** Spray through a vacuum line connected to the intake manifold (i.e. brake booster vacuum line) **3.** Go to step 4 below.

Non-Professional Users: 1. Warm up engine. **2.** For best results locate and spray **directly through the throttle body** (go to step 4). If space is tight, product may be sprayed upside-down. Avoid spraying sideways. If throttle body is not easily accessible, spray downstream of the MAF sensor. **3.** Fully engage (lift) the straw on the PermaStraw® Dual-Action Spray System and insert PAST the MAF sensor to avoid throwing a code. **4.** With engine running at 2,000 RPM, spray product in short bursts until can is empty. If necessary, accelerate to avoid engine stalling during spray period. DO NOT exceed 3,500 RPM. **5. Once can is empty, accelerate the engine 2 to 3 times without exceeding 3,500 RPM. 6. Run at idle for one minute, then turn engine off. 7.** Reassemble air intake system and let engine heat-soak for one hour. **8.** Restart engine and drive at highway speeds for at least 10 minutes.

CRC GDI IVD INTAKE VALVE & TURBO CLEANER is not a throttle body cleaner.
For the ***ULTIMATE*** fuel system cleanup, use this product followed by
CRC Throttle Body & Air-Intake Cleaner #05078 to clean the throttle body,
CRC MAF Sensor Cleaner #05110 to clean the MAF Sensor and ***CRC 1-TANK Power Renew® Complete Fuel System Cleanup #05815***, to clean the entire fuel system and restore power.

WARNING: Contains polyether amine, hydrocarbon propellant 68476-86-8, and petroleum distillates 64742-47-8, 64742-80-9, 64742-46-7. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120ºF. Exposure to high temperature may cause can to burst. Do not place in direct sunlight. Product is flammable and should be kept from all flames and other ignition sources. Avoid breathing of vapor and spray mist. Avoid contact with skin and eyes. Overexposure to liquid or vapors can cause severe irritation to eyes, skin, and upper respiratory tract, and central nervous system effects such as headache, dizziness or nausea. Product may pose an aspiration hazard if swallowed. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. Vapors are heavier than air and can accumulate in low areas. If you experience any symptoms listed on this label, increase ventilation or leave the area. This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. **FIRST AID:** If swallowed, DO NOT induce vomiting. Call physician immediately. In case of eye or skin contact, flush with water for at least 15 minutes. If too much is breathed, remove to fresh air. For all cases of overexposure, contact a physician. For additional information, consult SDS for this product. **DISPOSAL:** All used and unused product should be disposed of in conformance with local, state and federal regulations. **ELECTRICAL SHOCK HAZARD:** This can will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

KEEP AWAY FROM CHILDREN

©2016 CRC Industries, Inc., Warminster, PA 18974
www.crcindustries.com
Made in U.S.A. CRC#883A 16A DOT 2Q

800-521-3168 (Technical Information)
800-272-8963 (Customer Care)
215-442-6260 (SDS)

WORKS ON BOTH STANDARD AND DIRECT INJECTION ENGINES.
SAFE ON TURBOS AND INTERCOOLERS.

FLAMMABLE

0 78254 05319 6

CRC®

GDI IVD®

Intake Valve & Turbo Cleaner

Limpiador para válvula de admisión y turbo

EASY to Use! No intake manifold disassembly required

Restores Horsepower & MPG

PERMASTRAW® Dual-Action Spray System

Removes up to	More Concentrated	Highest %
46%	**150X**	**PEA**
Deposits in 1 Hour!	Than Fuel Additives	Detergency

REAL TESTS • REAL RESULTS • CRCGDI.COM

DANGER: FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. EYE AND SKIN IRRITANT. CONTENTS UNDER PRESSURE. READ WARNINGS ON BACK PANEL.

Net Wt. 11 oz (311 g) No. 05319