

**CRC**[®]**CONCENTRATED**

Radiator Sealer

One-Step Non-Acid Sealer**WARNING: MAY CAUSE EYE IRRITATION.
READ WARNINGS ON BACK PANEL.****PART NO. 05338**
Net Contents 12 fl. oz. (355 mL)

CRC RADIATOR SEALER

For use in all cooling systems. Quickly stops leaks in radiators and entire cooling system. Seals against seepage and prevents loss of anti-freeze. No clogging. Will not harm hoses or gaskets. Works with any standard anti-freeze or anti-rust solution.

DIRECTIONS: Read entire label before use. 1. With radiator nearly full, shake container thoroughly and add entire contents to radiator while engine is running at normal idle (it is not necessary to wait for engine warm-up). 2. Run engine at fast idle until leak stops. Do not drain. 3. One container is sufficient for cooling systems up to 22 quarts. If cooling system is not absolutely clean, use CRC Radiator Flush #05337. To resist future rust and corrosion, use CRC Radiator Anti-Rust #05335.

WARNING: Contains Water 7732-18-5, Naphthenic Oil 64742-53-6, Petroleum Sulfonate 64741-88-4, Bentonite 1302-78-9, Diatomaceous Earth 91053-39-3. Avoid continuous breathing of vapors. Avoid contact with skin and eyes. **FIRST AID:** In case of eye or skin contact, flush with large amounts of water for at least 15 minutes. If swallowed, do not induce vomiting. If too much is breathed, remove to fresh air. For severe overexposure, call a physician immediately. **KEEP AWAY FROM CHILDREN.**

For additional information, consult the Material Safety Data Sheet for this product. All used and unused product should be disposed of in conformance with local, state, and federal regulations.

©2002 CRC Industries, Inc., Warminster, PA 18974
800-521-3168 Technical Information
800-272-8963 Customer Service
215-442-6260 MSDS
Made in U.S.A.
02A CRC#639B
www.crcindustries.com

