



Gasoline Storage Stabilizer

- Preserves Stored Gasoline and Diesel Fuel
- For Use in Lawnmowers, Chainsaws, Boats, Motorcycles, Snowblowers, Garden Equipment and More

PART NO. 05360
Net Contents 12 fl. oz. (355 mL)

READ WARNINGS ON BACK PANEL.

CRC GASOLINE STORAGE STABILIZER

Concentrated, high-potency formula for use in all 2 and 4 cycle engine fuel tanks and gasoline storage containers. Keeps stored leaded and unleaded gasoline, gasohol and diesel fuel fresh for up to one year. Prevents gum and varnish build-up and keeps fuel system clean for optimum performance and easier starting over long storage. Reduces engine maintenance. No messy draining of fuel or fire hazard. Not a replacement for 2 Cycle Oil.

DIRECTIONS: Please read entire label before using this product.

Use one ounce per 1 gallon of fuel for storage period of up to 12 months. Pour Fuel Stabilizer into fuel. Run engine for 2-3 minutes to allow treated fuel to run through fuel system and engine. **FOR EVERYDAY USE:** Add 1 oz. for every 2 gallons of fuel.

WARNING: Contains Petroleum Distillate 64742-53-6 and organic additive (mixture). Avoid continuous breathing of vapor and spray mists. Avoid contact with skin and eyes. This product contains chemicals known to the State of California to cause cancer, birth defects and other reproductive harm.

FIRST AID: In case of eye contact, flush with water for 15 minutes. For skin contact, wash with soap and water. If swallowed **DO NOT** induce vomiting. If too much is breathed remove to fresh air. For severe overexposure call physician immediately.

KEEP AWAY FROM CHILDREN.

All used and unused product should be disposed of in conformance with local, state, and federal regulations.

For additional information, consult the Material Safety Data Sheet for this product.

©1998 CRC Industries, Inc., Warminster, PA 18974
800-521-3168 Technical Information
800-272-8963 Customer Service

Made in U.S.A.
CRC#587B
98A

