

CRC Silaramic® Brake System Grease is a pure silicone, dry-film, boundary (ceramic) lubricant formulated to reduce brake noise, vibrations and harshness (NVH) by dampening all brake vibrating frequencies. SILARAMIC Brake System Grease will stay in place and not run on friction pads or rotors in extreme temperature ranges from -50°F to over 3,000°F. Provides protection against dirt, corrosion and uneven pad wear. Repels brake dust. Displaces moisture. Meets Japanese rubber compatibility standard JIS K 2228 with EPDM & Nitrile rubbers.

DIRECTIONS: When rebuilding, assembling or installing brake components, thoroughly clean all brake parts with CRC Brakleen®. Wire brush and clean the caliper housing and backing plate to remove all dirt and dust using CRC BRAKLEEN. Apply SILARAMIC Brake System Grease to all moving caliper hardware, mating surfaces and backing plates – remove excess grease. **KEEP LUBRICANT OFF PADS AND ROTORS.**

HIGH TEMP • PURE SILICONE



SILARAMIC®
CERAMIC-FORTIFIED
BRAKE SYSTEM
GREASE
GRASA PARA EL SISTEMA DE FRENOS

NO. 05363

NET WT. 9 OZ. (255 g)

**EXTREME
TEMPERATURE
RANGE**
-50° TO 3000°F

**EPDM AND
NITRILE RUBBER
COMPATIBLE**

**IDEAL FOR
CERAMIC BRAKES
WHICH OPERATE
AT HIGHER TEMPS**

WARNINGS: Contains Polydimethylsiloxane 63148-62-9 and Magnesium silicate NJRTK# 80100362-5013P. Avoid contact with skin and eyes. May cause mild eye or skin irritation.

FIRST AID: In case of eye contact, flush with water for 15 minutes. In case of skin contact, wash with soap and water. If swallowed, DO NOT induce vomiting. For additional information, consult SDS for this product.

DISPOSAL: All used and unused product should be disposed of in conformance with local, state and federal regulations. Do not dump in sewers, floor drains, on the ground, or into any body of water.

KEEP AWAY FROM CHILDREN

©2013 CRC Industries, Inc.
Warminster, PA 18974
800-521-3168 (Technical Info)
800-272-8963 (Customer Service)
215-442-6260 (SDS)
www.crcindustries.com
Made in U.S.A. 13A

