

CRC Clean-R-Carb™ Carburetor Cleaner

For complete product usage instructions and safety warnings in Spanish, go to www.crcindustries.com. Para obtener las instrucciones completas de uso y advertencias de seguridad del producto en Español, visite www.crcindustries.com.

CRC Clean-R-Carb™ dissolves carburetor deposits such as gum, sludge and varnish to improve fuel system performance and insure maximum fuel economy. Safe for use with oxygen sensors and catalytic converters.

DIRECTIONS: Read entire label before using this product.

This product is extremely flammable and may cause flash fires and engine backfires which may result in injury. Do not spray on hot metal surfaces or when engine is hot. Use plastic extension tube to direct spray to exact location. **CARBURETOR AND LINKAGE:** With ignition off and engine cool, remove air filter and spray entire exterior surface of carburetor including linkage. After carburetor dries, start engine and spray CRC Clean-R-Carb™ down the carburetor throat to remove the deposits from the lower throttle plate area. **AUTOMATIC CHOKES:** With engine off, spray CRC Clean-R-Carb™ on both ends of choke valve and corresponding linkages while opening and closing choke by hand. **MANIFOLD HEAT CONTROL VALVE:** With engine cold, spray CRC Clean-R-Carb™ on both ends of heat control valve shaft. Move counterweight up and down until valve moves freely. If necessary, tap gently with a light hammer to loosen a frozen heat control valve. **PCV VALVE:** Disconnect crank case side of PCV valve and with engine running spray CRC Clean-R-Carb™ into open end of valve while working the plunger back and forth. **IMPORTANT:** if spilled or sprayed on painted surface, wipe off or wash off immediately.

WARNING: Contains Acetone 67-64-1, Heptane isomers 142-82-5, and Carbon dioxide 124-38-9. Do not puncture, incinerate or store can above 120°F. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Contents are extremely flammable. Vapors can accumulate and create a flammable atmosphere. Do not use near open flame or other sources of ignition. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. Overexposure to liquid or vapors can cause moderate to severe eye and skin irritation, irritation to upper respiratory tract, headache, dizziness, drowsiness or confusion. Deliberate misuse by concentrating and inhaling the contents can be harmful or fatal. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. Vapors are heavier than air and can accumulate in low areas. If you experience any symptoms listed on this label, increase ventilation or leave the area. Product may pose an aspiration hazard if swallowed. This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

FIRST AID: In case of eye or skin contact, flush with water for 15 minutes. If swallowed, DO NOT induce vomiting. If too much is breathed, remove to fresh air. For severe overexposure, call a physician immediately. For additional information, consult the Material Safety Data Sheet for this product. **DISPOSAL:** All used and unused product should be disposed of in conformance with local, state and federal regulations. Do NOT dump in sewers, floor drains, on the ground or into any body of water.

KEEP AWAY FROM CHILDREN

SPECIAL USAGE WARNINGS: Contents Extremely Flammable. Do not smoke while spraying. Extinguish all flames, pilot lights, and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until vapors are gone.

ELECTRICAL SHOCK HAZARD: This can will conduct electricity. Keep away from all live electrical sources including Battery Terminals, Solenoids, Electrical Panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

©2009 CRC Industries, Inc., Warminster, PA 18974
www.crcindustries.com
Made in U.S.A. CRC#920A/B 09A DOT 2Q

800-521-3168 (Technical Information)
800-272-8963 (Customer Service)
215-442-6260 (MSDS)

Professional users should consult MSDS and follow all applicable OSHA regulations.
Los usuarios profesionales deben consultar el MSDS y cumplir con todas las regulaciones de OSHA que correspondan.



Clean-R-Carb™ Carburetor Cleaner Limpiador de Carburador



50 State Formula
Fórmula 50 Estados

MEETS ALL STATE & FEDERAL VOC REGULATIONS

Cleans and Frees:

• Auto Chokes • Heat Risers • Carb Linkage • PCV System
Oxygen Sensor Safe

**Cumple con los reglamentos
VOC de todos los estados y el federal**

DANGER: EXTREMELY FLAMMABLE. VAPORS MAY CAUSE FLASH FIRES. HARMFUL OR FATAL IF SWALLOWED. EYE AND SKIN IRRITANT. CONTENTS UNDER PRESSURE. Read warnings on back panel.

PELIGRO: EXTREMADAMENTE INFLAMABLE. LOS VAPORES PUEDEN CAUSAR FOGONAZOS. NOCIVO O FATAL SI SE INGERE. IRRITA LA PIEL Y LOS OJOS. CONTENIDO BAJO PRESIÓN. Lea las advertencias en el dorso.

Net Wt. 12 oz. (340 g) No. 05379