



*Diesel*TM

Fuel Therapy[®]

**Diesel Injector Cleaner
with Anti-Gel**

Limpiador para Inyectores de Diesel con antigelificante

- *Provides Top-Tier Clean-Up with Max Treat*
- *Excellent Winter Protection*
- *Adds Lubricity to Low Sulfur Fuel*

**Treats
35
Gals.**

Part No. 05412

DANGER: COMBUSTIBLE,
HARMFUL OR FATAL IF SWALLOWED.
Read warnings on back panel.

12 fl oz (355 mL)



FUEL THERAPY® with Anti-Gel

For complete product usage instructions and safety warnings in Spanish, go to www.crcindustries.com. Para obtener las instrucciones completas de uso y advertencias de seguridad del producto en Español, visite www.crcindustries.com.

Emissions reducing formula rated "SUPERIOR" in Cummins L-10 test for injector cleanliness.

- Prevents Fuel Gelling • Increases MPG • Improves Power • Lowers Pour Point • Cleans Injectors
- Reduces Smoke • OK for Biodiesel • Prevents Corrosion • Stabilizes Fuel

This product complies with the federal ultra-low sulfur content requirements for use in all diesel motor vehicles and non-road engines. Contains no alcohol. Compatible with all diesel fuels. Improves cold weather starting.

DIRECTIONS: *Read entire label before using this product.* To reliquefy gelled fuel: 1. Remove diesel fuel filter. 2. Fill removed or new filter with FUEL THERAPY Diesel Injector Cleaner Plus w/Anti Gel. 3. Replace fuel filter. 4. Start engine. 5. Allow fuel system to circulate until full power is restored to engine. **For preventive maintenance and biodiesel fuels:** This container is sufficient to treat up to 35 gallons of diesel fuel, depending on fuel temperature. **To lower pour point,** the following ratios are recommended: • One bottle treats 18 gallons of fuel to lower pour point by as much as 35°F and CFPP by 31°F. • One bottle treats 35 gallons of fuel to lower pour point by as much as 15°F and CFPP by 24°F. For anticipated extreme conditions, add CRC DIESEL Cold Flow™ Anti-Gel with Lubricity (#05612) to fuel prior to temperature drop. For optimum performance, one bottle treats 18 gallons of fuel.

WARNING: Contains petroleum distillates 64742-80-9, 64742-94-5, 64742-54-7, mineral spirits 8052-41-3, and naphthalene 91-20-3. Product is combustible and should be kept from heat, open flames and other ignition sources. Do not store container above 100 °F. Avoid breathing vapor. Avoid contact with skin and eyes. Overexposure can cause irritation to eyes, skin, and upper respiratory tract, and headache or dizziness. Product may pose an aspiration hazard if swallowed. Use with adequate ventilation. This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. **FIRST AID:** In case of eye or skin contact, flush with water for 15 minutes. If swallowed, DO NOT induce vomiting. For severe overexposure, call physician immediately. For additional information, consult SDS for this product. **DISPOSAL:** All used and unused product should be disposed of in conformance with local, state and federal regulations. Do not dump in sewers, floor drains, on the ground, or into any body of water. **KEEP AWAY FROM CHILDREN**

©2015 CRC Industries, Inc., Warminster, PA 18974
www.crcindustries.com
Made in the U.S.A. CRC#927A 15A

800-521-3168 (Technical Information)
800-272-8963 (Customer Care)
215-442-6260 (SDS)

