




# FUEL THERAPY<sup>®</sup> with Anti-Gel

■ LOWERS POUR POINT & CFPP ■ RELIQUES GELLED FUEL

## Part No. 05425



05425

## NET WEIGHT 33 lb (15 kg)



### DANGER

Flammable liquid and vapor. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. Harmful if inhaled. May cause drowsiness or dizziness. Suspected of causing genetic defects. May cause damage to organs (nervous system) through prolonged or repeated exposure.

### PRECAUTIONARY STATEMENTS

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Do not breathe the mist or vapor. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Store in a well-ventilated place. Keep cool. Do not store container above 100 °F/38 °C. Store locked up. Dispose of contents/container in accordance with local/regional/national regulations.

### FIRST AID

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical attention. Wash contaminated clothing before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If exposed or concerned: Get medical attention. In case of fire: Do not use water jet as an extinguisher, as this will spread the fire.

This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

### DIRECTIONS: Read entire label before using this product.


For preventative maintenance and to lower pour point by as much as 15 °F and CFPP by 24 °F: 5 gallons treat 2500 gallons. To lower the pour point by as much as 35 °F and CFPP 31 °F and for biodiesel fuels: 5 gallons treats 1000 gallons. For anticipated extreme conditions, add CRC Diesel Cold Flow™ Anti-Gel with Lubricity (05632) to fuel prior to temperature drop.

This diesel fuel additive complies with the federal ultra-low sulfur content requirements for use in all diesel motor vehicles and non-road engines.

### HAZARDOUS MATERIAL IDENTIFICATION SYSTEM

HEALTH	2*	REACTIVITY	0
FLAMMABILITY	2	PERSONAL PROTECTION	B

HAZARD: MINIMAL=0 SEVERE=4



- Cleans Injectors
- Adds Lubricity
- Increases MPG
- OK for Biodiesel

Contains Diesel Fuel No. 2 (64742-80-9), Stoddard solvent (8052-41-3), Heavy aromatic solvent naphtha (64742-94-5), Hydrotreated heavy naphtha (64742-48-9) and Naphthalene (91-20-3).

©2016 CRC Industries, Inc.  
885 Louis Dr.

Warminster, PA 18974

800-521-3168 (Technical information)

800-272-8963 (Customer Care)

215-442-6260 (SDS)

www.crcindustries.com

16A CRC#892A Made in U.S.A.

FOR EMERGENCIES CALL CHEMTREC

1-800-424-9300

DATE  
CODE:



0 78254 05425 4