



DieselTM

Fuel Therapy[®]

Diesel Injector Cleaner with Anti-Gel

Limpiador para Inyectores de Diesel con antigelificante

- *Provides Top-Tier Clean-Up with Max Treat*
- *Excellent Winter Protection*
- *Adds Lubricity to Low Sulfur Fuel*

**Treats
125
Gals.**

DANGER: COMBUSTIBLE.
HARMFUL OR FATAL IF
SWALLOWED.

Read warnings on back panel.

Part No. 05432

1 pt 14 fl oz / 30 fl oz (888 mL)



FUEL THERAPY® with Anti-Gel

For complete product usage instructions and safety warnings in Spanish, go to www.crcindustries.com. Para obtener las instrucciones completas de uso y advertencias de seguridad del producto en Español, visite www.crcindustries.com.

Emissions reducing formula rated "SUPERIOR" in Cummins L-10 test for injector cleanliness. OK for biodiesel.

- Prevents Fuel Gelling
- Lowers Pour Point
- Adds Lubricity
- Increases MPG
- Cleans Injectors
- Prevents Corrosion
- Improves Power
- Reduces Smoke
- Stabilizes Fuel

This product complies with the federal ultra-low sulfur content requirements for use in all diesel motor vehicles and non-road engines.

CRC DIESEL Fuel Therapy® is non-corrosive and contains no alcohol. Compatible with all diesel fuels. Improves cold weather starting.

DIRECTIONS: Read entire label before using this product. To reliquefy gelled fuel: 1. Remove diesel fuel filter. 2. Fill removed or new filter with FUEL THERAPY Diesel Injector Cleaner w/Anti Gel. 3. Replace fuel filter. 4. Start engine. 5. Allow fuel system to circulate until full power is restored to engine. For preventive maintenance and biodiesel fuels: This container is sufficient to treat up to 125 gallons of diesel fuel, depending on fuel temperature. To lower pour point, the following ratios are recommended: (For biodiesel fuels, use 50 gallon treat.)

- One bottle treats 50 gallons of fuel to lower pour point by as much as 35°F and CFPP by 31°F.
 - One bottle treats 125 gallons of fuel to lower pour point by as much as 15°F and CFPP by 24°F.
- For anticipated extreme conditions, add CRC DIESEL Cold Flow™ Anti-Gel with Lubricity (#05632) to fuel prior to temperature drop. For optimum performance, one bottle treats 50 gallons of fuel.

WARNING: Contains petroleum distillates 64742-80-9, 64742-94-5, 64742-48-9, mineral spirits 8052-41-3, and naphthalene 91-20-3. Product is combustible and should be kept from heat, open flames and other ignition sources. Avoid continuous breathing of vapor. Avoid contact with skin and eyes. Overexposure to liquid or vapors can cause irritation to eyes, skin, and upper respiratory tract, and central nervous system effects such as headache or dizziness. Use with adequate ventilation. Product may pose an aspiration hazard if swallowed. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. Do not store container above 100 °F. This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. **FIRST AID:** In case of eye or skin contact, flush with water for 15 minutes. If swallowed, DO NOT induce vomiting. If too much is breathed, remove to fresh air. For severe overexposure, call physician immediately. For additional information, consult SDS for this product. **DISPOSAL:** All used and unused product should be disposed of in conformance with local, state and federal regulations. Do not dump in sewers, floor drains, on the ground, or into any body of water. **KEEP AWAY FROM CHILDREN**

