

COOLING SYSTEM FORMULA

Tow Kool™ is scientifically developed to reduce operating temperatures, maximize cooling system efficiency and increase cooling system component life in tow vehicles, trucks, SUV's and passenger cars.



Directions: Read entire label before using this product. Shake well before using.

Note: Optimum performance is achieved with a leak-free and well maintained cooling system.

1. Make sure vehicle is off and cooling system is completely cool.
2. If necessary, drain 16 ounces of coolant to allow room for Tow Kool™. (See disposal statement) If rust, scale or contamination is found, it is recommended that the system be drained and flushed. Use CRC's One-Step Radiator Flush, item number 05377.
3. Add one 16-ounce bottle of concentrated Tow-Kool™ for Cooling Systems to the vehicle's radiator or recirculation tank. Ensure coolant is up to the manufacturer's suggested fill level. Use every 12,000 miles.
4. For large capacity radiators, use one 16-ounce bottle for every 20 quarts of coolant.

WARNING: Contains Water 7732-18-5, Propylene Glycol 57-55-6, Sodium Nitrite 7632-00-0, Polyethylene Glycol 9003-13-8 and Ethoxylated Castor Oil 61791-12-6. **DO NOT SWALLOW!** May be harmful or fatal. May irritate mouth, throat and stomach if swallowed. May irritate eyes if splashed. This product contains chemicals known to the state of California to cause cancer, birth defects and other reproductive harm.

FIRST AID: If swallowed give one or two glasses of water and call a doctor for instructions to induce vomiting. If splashed in eyes, rinse thoroughly with water.


KEEP AWAY FROM CHILDREN.

All used and unused product should be disposed of in conformance with local, state and federal regulations.

For additional information, consult the Material Safety Data Sheet for this product.

©2001 CRC Industries, Inc.
Warminster, PA 18974
800-521-3168 (Technical Information)
800-272-8963 (Customer Service)
215-442-6260 (MSDS)
www.crcindustries.com

01B
Made in U.S.A.
CRC #614B



- ◆ Reduces Operating Temperatures
- ◆ Prevents Overheating
- ◆ Lubricates Cooling System
- ◆ Improves Air-Conditioner Performance

No. 05501

CAUTION:

Read Warnings on Back Panel.

Net Contents 16 fl. oz. (474 mL)

