

# TOW KOOL™

- ◆ Revitalizes ATF Viscosity
- ◆ Extends Transmission Fluid Life
- ◆ Reduces Transmission Temperatures
- ◆ All ATF Compatible

FOR  
AUTOMATIC  
TRANSMISSIONS

No. 05502

**CAUTION:**

Read Warnings on Back Panel.

Net Contents 16 fl. oz. (474 mL)

**CRC**

## AUTOMOTIVE TRANSMISSION FORMULA

The majority of transmission failures are caused by overheating and fluid breakdown. **Tow Kool™** is scientifically developed to lower transmission temperatures, revitalize fluid viscosity and extend transmission fluid life in tow vehicles, trucks, SUV's and passenger cars.

**Directions:** Read entire label before using this product.  
**Shake well before using.**

**Note:** Optimum performance is achieved with a leak-free and well maintained transmission.

1. Make sure vehicle is not running, cool and in park.
2. If necessary, drain 16 ounces of transmission fluid to allow room for Tow Kool™. (See disposal statement).  
Tips for draining an automatic transmission without a drain plug ...
  - Use the Sta-Lube® Fluid Oil Pump (Item number SL4344) and siphon 16 ounces of ATF through the dip stick/filler tube.
  - Using a line wrench, carefully disconnect the transmission line at the radiator or an external cooler and drain into a receptacle.
3. Add one 16-ounce bottle of Tow-Kool™ for Automatic Transmissions to the transmission through the dip stick/filler tube. One bottle treats 9 quarts of ATF.
4. Start vehicle. Follow manufacturers recommended procedures and check to ensure ATF fluid level is full. Add ATF if necessary. Do not overfill.

**WARNING:** Contains Polymethacrylate, Mineral Oil 64742-54-7, Alkylated phenol 128-39-2, Alkylphosphite 800967-5534. This product contains chemicals known to the state of California to cause cancer, birth defects and other reproductive harm. **FIRST AID:** If ingested, do not induce vomiting. Call a physician.

**KEEP AWAY FROM CHILDREN.**

All used and unused product should be disposed of in conformance with local, state and federal regulations.

For additional information, consult the Material Safety Data Sheet for this product.

©2001 CRC Industries, Inc.  
Warminster, PA 18974  
800-521-3168 (Technical Information)  
800-272-8963 (Customer Service)  
215-442-6260 (MSDS)  
www.crcindustries.com

O1A  
Made in U.S.A.  
CRC #549



2