



Premium Air Brake Conditioner

■ PREVENTS ICING

■ PROTECTS AGAINST CORROSION

Part No. 05525

NET WEIGHT 33.1 lbs. (15 Kg)

HANDLING AND SPILL PRECAUTIONS: Keep container closed. Do not store bulk container above 80°. Wash thoroughly after handling. Do not enter where vapors are suspected in high concentration unless air supplied positive pressure breathing apparatus is used and a trained observer is present and equipped with rescue gear. **FOR SPILLS,** use proper protective equipment. Take precautions as necessary to prevent contamination of ground or surface water. For small spills, use absorbent and sweep into closed containers for disposal. For large spills, evacuate the area, dike and transfer into containers for disposal. **DISPOSAL:** Used and unused contents and containers must be disposed of in accordance with all federal, state, and local regulations. **EMPTY** containers may be offered to a qualified reconditioner. Unused contents may be offered to a licensed reclaimers. Do not dump into sewers, on the ground, or into any body of water.

DIRECTIONS: Please read entire label before using this product. For filling alcohol evaporators - fill jar about 2/3 full of CRC Premium Air Brake Conditioner. When compressor is compressing air, bubbles should be passing through Air Brake Conditioner. Check to insure all connections are tight, and that filter cap and cover are in good condition.

FIRST AID: In case of eye or skin contact, flush with water for 15 minutes. If swallowed, **DO NOT** induce vomiting. If too much is breathed, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. For severe overexposure, call a physician immediately.

CAUTION: Empty containers retain residue (liquid and/or vapor) and can be dangerous. **DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE THIS CONTAINER TO HEAT, FLAME, SPARKS, OR OTHER SOURCES OF IGNITION: IT MAY EXPLODE AND CAUSE INJURY OR DEATH.** Do not attempt to clean, since residue is difficult to remove. Empty drums should be completely drained, promptly bunged, and promptly returned to a drum reconditioner.

Use only in a well ventilated area. For additional information, consult the Material Safety Data Sheet for this product.

KEEP AWAY FROM CHILDREN

DANGER: FLAMMABLE. VAPOR HARMFUL. MAY BE FATAL OR CAUSE BLINDNESS IF SWALLOWED. Read warnings carefully.

- Complete Winter Protection for Air Brake Systems
- Anti-Freeze & Anti-Rust
- Keeps Air Tanks Moisture Free
- Replaces #406005

DANGER: POISON. Contains Methanol 67-56-1. Cannot be made non-poisonous. Avoid contact with eyes. Use only in a well ventilated area. Keep away from heat and flame.

©2002 CRC Industries, Inc.
Warminster, PA 18974
800-521-3168 (Technical information)
800-272-8963 (Customer Service)
215-442-6260 (MSDS)
www.crcindustries.com
02A CRC#620B Made in U.S.A.
FOR EMERGENCIES CALL CHEMTREC
1-800-424-9300

HEALTH	3	REACTIVITY	0
FLAMMABILITY	3	PERSONAL PROTECTION	B

HAZARD: MINIMAL=0 SEVERE=4

