



*Diesel*TM

Cold FlowTM

Anti-Gel with Lubricity

Antigelificante lubricado

- *Lowers Pour Point and CFPP*
- *Prevents Diesel Gelling*

**Treats
125
Gals.**

**DANGER: FLAMMABLE, VAPOR HARMFUL,
HARMFUL OR FATAL IF SWALLOWED.**
Read warnings on back panel.



Part No. 05612
Net Contents 12 fl. oz. (355 mL)



COLD FLOW™ Anti-Gel with Lubricity

For complete product usage instructions and safety warnings in Spanish, go to www.crcindustries.com. Para obtener las instrucciones completas de uso y advertencias de seguridad del producto en Español, visite www.crcindustries.com.

Cold Flow Anti-Gel with Lubricity is formulated for cold weather use in all diesel equipment. Assures superior performance in winter without harmful alcohol. Lowers fuel pour point by as much as 40°F. Retards gelling or waxing during cold weather. Disperses water. Cleans injectors. OK for biodiesel.

This product complies with the federal ultra-low sulfur content requirements for use in all diesel motor vehicles and non-road engines. Compatible with all diesel fuels.

DIRECTIONS: Read entire label before using this product.

1. Before outside temperature drops to 50°F (10°C), add one container for each 125 gallons of diesel or biodiesel fuel. 2. For passenger cars, add six ounces per 25 gallons. 3. Mix thoroughly. Change fuel filters.

WARNING: Contains Xylene 1330-20-7, Petroleum naphtha 64742-94-5, Ethylbenzene 100-41-4, Tall oil fatty acid 61790-12-3 and Naphthalene 91-20-3. Product is flammable and should be kept from open flames and other ignition sources. Avoid breathing vapors. Avoid skin and eye contact with liquid. Overexposure to liquid or vapors can cause irritation to eyes, skin, and upper respiratory tract, and central nervous system effects such as headache or dizziness. High concentrations have caused liver and kidney effects in laboratory animals. Product may pose an aspiration hazard if swallowed. Use with adequate ventilation. If you experience any symptoms listed on this label, increase ventilation or leave the area. This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. **FIRST AID:** In case of eye or skin contact, flush with water for 15 minutes. If swallowed, DO NOT induce vomiting. If too much is breathed, remove to fresh air. For severe overexposure, call physician immediately. For additional information, consult MSDS for this product. **DISPOSAL:** All used and unused product should be disposed of in conformance with local, state and federal regulations. Do not dump in sewers, floor drains, on the ground, or into any body of water.

KEEP AWAY FROM CHILDREN

© 2010 CRC Industries, Inc.
Warminster, PA 18974
800-521-3168 (Technical Information)
800-272-8963 (Customer Service)

Made in the U.S.A
10A CRC#0929
215-442-6260 (MSDS Faxback)
www.crcindustries.com

SILOO

CRC DIESEL #05612
FORMERLY SILOO #65A

