



COLD FLOW™ Anti-Gel with Lubricity

■ LOWERS POUR POINT BY UP TO 40°F ■ PREVENTS DIESEL FUEL GELLING

Part No. 05625

NET WEIGHT 35.3 lbs. (16 Kg)

HANDLING AND SPILL PRECAUTIONS: Keep container closed. Do not store bulk container above 80°. Wash thoroughly after handling. Do not enter where vapors are suspected in high concentration unless air supplied positive pressure breathing apparatus is used and a trained observer is present and equipped with rescue gear. FOR SPILLS, use proper protective equipment. Take precautions as necessary to prevent contamination of ground or surface water. For small spills, use absorbent and sweep into closed containers for disposal. For large spills, evacuate the area, dike and transfer into containers for disposal. DISPOSAL: Used and unused contents and containers must be disposed of in accordance with all federal, state, and local regulations. EMPTY containers may be offered to a qualified reconditioner. Unused contents may be offered to a licensed reclaimer. Do not dump into sewers, on the ground, or into any body of water.

DIRECTIONS: Read entire label before using this product. Before outside temperature drops to 50°F (10°C), add one gallon CRC Premium Anti-Gel w/ Lubricity to each 1000 gallons of diesel fuel to obtain maximum pour point reduction. Depending on type of fuel, pour point can be lowered by as much as 40°F & CFPP by 25°F.

To help treat fuel mildly gelled, add two or three gallons Anti-Gel per 1000 gallons of diesel fuel. Mix thoroughly. Change fuel filter. Usage in excess of recommended quantity will not be harmful.

FIRST AID: In case of eye or skin contact, flush with water for 15 minutes. If swallowed, DO NOT induce vomiting. If too much is breathed, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. For severe overexposure, call a physician immediately.

CAUTION: Empty containers retain residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE THIS CONTAINER TO HEAT, FLAME, SPARKS, OR OTHER SOURCES OF IGNITION: IT MAY EXPLODE AND CAUSE INJURY OR DEATH. Do not attempt to clean, since residue is difficult to remove. Empty drums should be completely drained, promptly bunged, and promptly returned to a drum reconditioner.

Use only in a well ventilated area. This product contains chemicals known to the State of California to cause cancer, birth defects and other reproductive harm. For additional information, consult the Material Safety Data Sheet for this product.

KEEP AWAY FROM CHILDREN

DANGER: FLAMMABLE. VAPOR HARMFUL. HARMFUL OR FATAL IF SWALLOWED.
Read warnings carefully.

- Concentrated Anti-Gel
- Lowers CFPP
- Disperses Water
- Replaces #65C, #405505

WARNING: Contains Petroleum Distillate 64742-95-6, Xylene 1330-20-7, Copolymer Resin 800967-5483P, Ethylbenzene 100-41-4, Trimethylbenzene (isomers) 25551-13-7 and Detergent (mixture).

©2003 CRC Industries, Inc.
Warminster, PA 18974
800-521-3168 (Technical information)
800-272-8963 (Customer Service)
215-442-6260 (MSDS)
www.crcindustries.com
03A CRC#627F Made in U.S.A.
FOR EMERGENCIES CALL CHEMTREC
1-800-424-9300

HEALTH	2	REACTIVITY	0
FLAMMABILITY	3	PERSONAL PROTECTION	B

HAZARD: MINIMAL=0 SEVERE=4

