




COLD FLOW™ Anti-Gel with Lubricity

■ LOWERS POUR POINT BY UP TO 40°F ■ PREVENTS DIESEL FUEL GELLING



Part No. 05655

NET WEIGHT 390 lbs. (177 kg)



DANGER

Flammable liquid and vapor. May be fatal if swallowed and enters airways. Causes skin irritation. Causes eye irritation. May cause respiratory irritation. Suspected of causing cancer. Suspected of damaging fertility or the unborn child.

PRECAUTIONARY STATEMENTS

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing mist or vapor. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up. Do not store container above 100 °F/38 °C. Dispose of contents/container in accordance with local/regional/national regulations. In case of fire: Do not use water jet as an extinguisher, as this will spread the fire.

HEALTH	2*	REACTIVITY	0
	3	PERSONAL PROTECTION	B

HAZARD: MINIMAL=0 SEVERE=4

- Concentrated Anti-Gel
- Lowers CFPP
- Disperses Water
- OK for Biodiesel

Contains Xylene (1330-20-7), Ethylbenzene (100-41-4), Heavy aromatic solvent naphtha (64742-94-5), 1,2,4-Trimethylbenzene (95-63-6) and Naphthalene (91-20-3).

©2015 CRC Industries, Inc.
Warminster, PA 18974
800-521-3168 (Technical information)
800-272-8963 (Customer Service)
215-442-6260 (SDS)
www.crcindustries.com
15A CRC#627K Made in U.S.A.
FOR EMERGENCIES CALL CHEMTREC
1-800-424-9300

Batch #:
Date Code:



FIRST AID

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical attention. Wash contaminated clothing before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If exposed or concerned: Get medical attention.

This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

DIRECTIONS: Please read entire label before using this product.

Before outside temperature drops to 50°F (10 °C), add one gallon CRC Premium Anti-Gel w/ Lubricity to each 1000 gallons of diesel or biodiesel fuel to obtain maximum pour point reduction. Depending on type of fuel, pour point can be lowered by as much as 40 °F & CFPP by 25 °F. For optimum treat of biodiesel fuels or to help treat fuel mildly gelled, add two or three gallons Anti-Gel per 1000 gallons of diesel fuel. Mix thoroughly. Change fuel filter. Usage in excess of recommended quantity will not be harmful.

This diesel fuel additive complies with the federal ultra-low sulfur content requirements for use in all diesel motor vehicles and non-road engines.