



LubriCure™ Concentrated Lubricity Improver

For complete product usage instructions and safety warnings in Spanish, go to www.crcindustries.com. Para obtener las instrucciones completas de uso y advertencias de seguridad del producto en Español, visite www.crcindustries.com.

Replaces the lubricity lost by the sulfur reduction in Ultra-Low Sulfur Diesel Fuel.

- **Protects diesel pumps & injectors from premature wear**
- **Use with every fill-up for maximum protection**
- **Excellent SLBOCLE (ASTM D 6078) and ASTM HFRR 460 Lubricity Specification**

This product complies with the federal ultra-low sulfur content requirements for use in all diesel motor vehicles and non-road engines.

DIRECTIONS: *Read entire label before using this product.* 1. One bottle treats 125 gallons of diesel fuel. 2. Pour entire bottle into diesel tank. 3. For optimum protection, use with every fill-up.

WARNING: Contains Stoddard Solvent 8052-41-3, Petroleum Distillate 68476-34-6, Tall Oil Fatty Acid 61790-12-3, Isopropyl Alcohol 67-63-0 and an additive blend. Overexposure to vapor may cause eye and skin irritation, irritation of respiratory tract, headaches, dizziness, anesthesia, drowsiness, unconsciousness and other central nervous system effects. Product is flammable and should be kept from all flames and other ignition sources. This product contains chemicals known to the State of California to cause cancer, birth defects and other reproductive harm. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid continuous breathing of vapors. Avoid contact with skin and eyes. **FIRST AID:** In case of eye contact, flush with water for 15 minutes. If swallowed, DO NOT induce vomiting. If too much is breathed remove to fresh air. For severe overexposure, call a physician immediately.

KEEP AWAY FROM CHILDREN

For additional information, consult the Material Safety Data Sheet for this product. All used and unused product should be disposed of in conformance with local, state and federal regulations. DO NOT dump in sewers, floor drains, on the ground, or into any body of water.

©2009 CRC Industries, Inc., Warminster, PA 18974
www.crcindustries.com
Made in U.S.A. CRC# 0690A 09A

800-521-3168 (Technical Information)
800-272-8963 (Customer Service)
215-442-6260 (MSDS)



LubriCure™

Concentrated Lubricity Improver

Mejorador concentrado de lubricación

- **For Ultra-Low Sulfur Diesel Fuel**
- **Reduces Engine Wear**
- **Protects Diesel Fuel Pump & Fuel Injectors**
- **Use With Every Fill-up**

Treats
125
Gals.

**DANGER: FLAMMABLE. HARMFUL
OR FATAL IF SWALLOWED.**

Read warnings on back panel. Net Contents 12 fl. oz. (355 mL)

Part No. 05712