

Battery Terminal Protector

Para obtener información adicional en Español, visite www.crcindustries.com.

This lead-free protective coating formula is specifically designed to protect battery terminals from corrosion, which is a major cause of hard starting and battery failure.

DIRECTIONS: Read entire label before using this product.

Apply after battery has been connected. 1. Shake can well before using. 2. Clean away existing corrosion with CRC® Battery Cleaner, item #05723. 3. Apply an even coat to freshly cleaned hold-downs, bolts, brackets and terminals. 4. For preventive maintenance, reapply when red film turns clear. 5. When finished spraying, clean valve by turning can upside down and depressing actuator until only propellant escapes.

WARNING: Contains heptane-hexane blend (64742-49-0, 589-34-4, 142-82-5, 591-76-4, 108-87-2 & 110-54-3), xylene 1330-20-7, ethylbenzene 100-41-4, and liquefied petroleum gas 68476-86-8. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F/49°C. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Avoid breathing of vapor and contact with skin and eyes. Overexposure to liquid or vapors can irritate eyes, skin and upper respiratory tract, and may cause headache, dizziness, or drowsiness. Product may pose an aspiration hazard if swallowed. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. Vapors are heavier than air and can accumulate in low areas. If you experience any symptoms listed on this label, increase ventilation or leave the area.

SPECIAL USAGE WARNINGS: Contents extremely flammable. Do not smoke while spraying. Extinguish all flames, pilot lights, and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until vapors are gone.

FIRST AID: In case of eye or skin contact, flush with water for 15 minutes. If too much is breathed, remove to fresh air. If swallowed, call your poison control center at 1-800-222-1222.

DISPOSAL: All used and unused product should be disposed of in conformance with local, state and federal regulations.

KEEP AWAY FROM CHILDREN

ELECTRICAL SHOCK HAZARD: This metal can will conduct electricity. Keep away from all live electrical sources. Failure to observe this warning may result in serious injury and/or flash fire.



WARNING: This product can expose you to chemicals including naphthalene which is known to the State of California to cause cancer and to toluene which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

©2016 CRC Industries, Inc., Warminster, PA 18974
www.crcindustries.com
Made in USA 16A CRC#597P/Q

VOC Category: Electrical Coating MIR Limit: 2.0

800-272-8963 Customer Care
800-521-3168 Technical Info
215-442-6260 SDS

CRC

TECHNICIAN GRADE

Battery Terminal Protector

Prevents Corrosion

PROTECTOR DE
TERMINALES DE BATERÍA



Prolongs Battery Life • Assures Easier Starting



DANGER: EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. CONTENTS UNDER PRESSURE. READ WARNINGS ON BACK PANEL.

Net Wt. 7.5 oz (213 g) No. 05746