



*Diesel*<sup>™</sup>

# **1 TANK** **POWER RENEW**<sup>®</sup>

**with G2P<sup>®</sup> Technology**

Tratamiento para sistema de combustible diesel



- **Concentrated Diesel & Emissions Systems Cleanup**
- **3X More Potent than Leading Brands**
- **Maximum Power Restoration & Deposit Control**
- **Excellent Cleanup for Modern Common Rail Systems**

**Complete  
Cleanup in One  
Tank!**

**DANGER: HARMFUL OR FATAL IF SWALLOWED. MAY CAUSE EYE AND SKIN IRRITATION. READ WARNINGS ON BACK PANEL.**

Part No. 05832

**31 fl oz (917 mL)**



# 1-TANK Power Renew<sup>®</sup> with G2P<sup>®</sup> Technology

For complete product usage instructions and safety warnings in Spanish, go to [www.crcindustries.com](http://www.crcindustries.com). Para obtener las instrucciones completas de uso y advertencias de seguridad del producto en Español, visite [www.crcindustries.com](http://www.crcindustries.com).

**Featuring G2P<sup>®</sup> technology, this breakthrough formula provides TOTAL 100% deposit removal and power restoration, proven by exceeding industry standard tests: XUD-9 and CEC DW10 engine tests.**

- Unparalleled one-tank cleanup
- Restores lost power
- Helps increase MPG
- Boosts power
- Cleans injectors and prevents fouling
- Helps free sticky injectors
- Reduces exhaust emissions
- Works great in BIODIESEL blends

***This product complies with the federal ultra-low sulfur content requirements for use in all diesel motor vehicles and non-road engines. Compatible with all diesel and biodiesel blends up to B20.***

**DIRECTIONS:** *Read entire label before using this product.*

For best results, use every three months. TRUCKS: One bottle treats 125 gallons of diesel fuel. Pour one bottle into a full tank of diesel fuel. BUSES: Use ½ bottle to treat 60 gallons of diesel fuel. PASSENGER VEHICLES: Use ¼ bottle (8 oz.) to treat 30 gallons of diesel fuel.

**WARNING:** Contains 2-ethylhexyl nitrate 27247-96-7, petroleum distillates 64742-47-8 & 64742-54-7 and 2-ethylhexanol 104-76-7. Product is combustible and should be kept from heat, open flames and other ignition sources. Avoid continuous breathing of vapor. Avoid contact with skin and eyes. Overexposure to liquid or vapors can cause irritation to eyes, skin, and upper respiratory tract, and central nervous system effects such as headache or dizziness. Product may pose an aspiration hazard if swallowed. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

**FIRST AID:** In case of eye or skin contact, flush with water for 15 minutes. If too much is breathed, remove to fresh air. If swallowed, DO NOT induce vomiting. For severe overexposure, call physician immediately. For additional information, consult SDS for this product. **DISPOSAL:** All used and unused product should be disposed of in conformance with local, state and federal regulations. Do not dump in sewers, floor drains, on the ground, or into any body of water.

**KEEP AWAY FROM CHILDREN**



©2015 CRC Industries, Inc.  
Warminster, PA 18974  
[www.crcindustries.com](http://www.crcindustries.com)  
Made in the U.S.A.

15A CRC#908E

800-521-3168 (Technical Information)  
800-272-8963 (Customer Care)  
215-442-6260 (SDS Faxback)  
**CRC DIESEL #05832**