




# QUICK FLOW™ Emergency Diesel-Gel Relief

■ QUICKLY DISSOLVES GELLED FUEL ■ THAWS FROZEN FUEL FILTERS

Part No. 05955



NET WEIGHT 355 lbs. (161 kg)



### DANGER

Flammable liquid and vapor. May be fatal if swallowed and enters airways.  
May cause drowsiness or dizziness.

### PRECAUTIONARY STATEMENTS

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Avoid breathing mist or vapor. Wear protective gloves/protective clothing/eye protection/face protection. Store in a well-ventilated place. Keep cool. Do not store container above 100 °F/38 °C. Store locked up. Dispose of contents/container in accordance with local/regional/national regulations. In case of fire: Use appropriate media to extinguish.

### FIRST AID

If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.

This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. Deliberate misuse by concentrating and inhaling the contents is illegal and can be harmful or fatal. Inhalation abuse can cause death. For additional information, consult SDS for this product.

### DIRECTIONS: Read entire label before using this product.

For emergency use: 1. Remove diesel fuel filter. 2. Fill removed or new filter with Quick Flow™ Emergency Fuel-Gel Relief. 3. Replace fuel filter. 4. Start engine. 5. Allow fuel system to circulate until full power is restored to the engine. 6. If fuel in tanks is gelled, also add 1 qt. of Quick Flow™ to every 30 gallons of fuel in the tanks. For preventative maintenance and to lower pour point by as much as 15°F and CFPP by 24°F: 5 gallons treat 2500 gallons. To lower the pour point by as much as 35°F and CFPP 31 °F and for biodiesel fuels: 5 gallons treats 1000 gallons. For anticipated extreme conditions, add CRC Diesel Cold Flow™ Anti-Gel with Lubricity (05632) to fuel prior to temperature drop.

This diesel fuel additive complies with the federal ultra-low sulfur content requirements for use in all diesel motor vehicles and non-road engines.

HEALTH	1*	REACTIVITY	0
	FLAMMABILITY		PERSONAL PROTECTION
		2	B

HAZARD: MINIMAL=0 SEVERE=4

- Quickly Dissolves Gelled Fuel
- Thaws Frozen Fuel Filters
- Protects Against Gelling
- OK for Biodiesel

Contains Stoddard solvent (8052-41-3), Heavy aromatic solvent naphtha (64742-94-5), 1,2,4-Trimethylbenzene (95-63-6) and Naphthalene (91-20-3).

©2015 CRC Industries, Inc.  
Warminster, PA 18974  
800-521-3168 (Technical information)  
800-272-4620 (Customer Care)  
215-442-6260 (SDS)  
www.crcindustries.com  
15A CRC#673C Made in U.S.A.  
FOR EMERGENCIES CALL CHEMTREC  
1-800-424-9300

Batch No.:  
Date Code:

