



# Engine Stor<sup>®</sup> Fogging Fluid

■ Fogging Fluid for Seasonal Motor Storage

■ Long Term Metal Protection

Part No. 06070



NET WEIGHT: 37 lbs. (16.8 Kg)

**HANDLING AND SPILL PRECAUTIONS:** Keep container closed. Wash thoroughly after handling. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. **FOR SPILLS,** use proper protective equipment. Take precautions as necessary to prevent contamination of ground or surface water. For small spills, use absorbent and sweep into closed containers for disposal. For large spills, evacuate the area, dike and transfer into containers for disposal.

**DISPOSAL:** Used and unused contents and containers must be disposed of in accordance with all federal, state, and local regulations. **EMPTY** containers may be offered to a qualified reconditioner. Unused contents may be offered to a licensed reclaimer. Do not dump into sewers, on the ground, or into any body of water.

**READ WARNINGS CAREFULLY.**

**FIRST AID:** In case of eye or skin contact, flush with water for 15 minutes. If swallowed, **DO NOT** induce vomiting. If too much is breathed, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. For severe overexposure, call a physician immediately. **CAUTION:** Empty containers retain residue (liquid and/or vapor) and can be dangerous. **DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE THIS CONTAINER TO HEAT, FLAME, SPARKS, OR OTHER SOURCES OF IGNITION: IT MAY EXPLODE AND CAUSE INJURY OR DEATH.** Do not attempt to clean, since residue is difficult to remove. Empty drums should be completely drained, promptly bunged, and promptly returned to a drum reconditioner.

For additional information, consult the Material Safety Data Sheet for this product. **KEEP OUT OF REACH OF CHILDREN.**

- Protects outboard motors, marine engines, and internal combustion engines to insure longer life.
- Keeps pistons, rings and cylinder walls corrosion free. Protects electrical connections in use or in storage.

**WARNING:** Contains Napthenic distillates 64742-52-5/64742-53-6, Ihibited Paraffinic Oil 64741-88-4/123-95-5.

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM

HEALTH	<b>1</b>	REACTIVITY	<b>0</b>
FLAMMABILITY	<b>1</b>	PERSONAL PROTECTION	<b>B</b>

HAZARD: MINIMAL=0 SEVERE=4

**Read warnings carefully.**

©2006 CRC Industries, Inc.  
 Warminster, PA 18974  
 800-521-3168 (Technical information)  
 800-272-4620 (Customer Service)  
 215-442-6260 (MSDS)  
 www.crcindustries.com  
 06A CRC#537B Made in U.S.A.  
**FOR EMERGENCIES CALL CHEMTREC**  
 1-800-424-9300

