

Heavy Duty Silicone™

NAPA/CRC HEAVY DUTY SILICONE is a non-corrosive, VOC compliant formula that lubricates and eliminates squeaking and binding caused by friction. Its film is clean, odorless, and highly resistant to water. Its lubricating properties are retained as low as -40°F and as high as 400°F.

• Lubricates metal, rubber, nylon and wood. • **NOT FOR USE ON PLASTICS.** • Protects and lubricates tools, jacks, hoists, locks, latches, seat adjusters, zippers, springs and pulleys. • Meets FDA Regulation CFR-21-178.3570 for lubricants with incidental food contact.

DIRECTIONS: *Read entire label before using this product.* 1. Do not apply while equipment is energized. 2. Cover and protect plastic and painted surfaces from overspray. Check on small area before using. Not for use on automotive interiors. 3. Apply light, even film. 4. Hold can 8" to 10" away from surface to be sprayed. 5. Use extension tube for pinpoint accuracy. 6. Wipe off excess with cloth. 7. Repeat applications periodically.

WARNING: Contains Acetone 67-64-1, Heptane 142-82-5, Polydimethylsiloxane 63148-62-9 and Hydrocarbon propellant 68476-86-8. Do not puncture, incinerate or store can above 120°F. Exposure to high temperature may cause can to burst. Do not place in direct sunlight or near any heat source. Contents are extremely flammable. Do not use near open flame or other sources of ignition. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. Overexposure to liquid or vapors can cause moderate to severe eye and skin irritation, irritation to upper respiratory tract, and central nervous system effects such as headache, dizziness, drowsiness, or confusion. Deliberate misuse by concentrating and inhaling the contents can be harmful or fatal. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. Vapors are heavier than air and can accumulate in low areas. If you experience any symptoms listed on this label, increase ventilation or leave the area. Product may pose an aspiration hazard if swallowed. This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm. **FIRST AID:** In case of eye or skin contact, flush with water for 15 minutes. If swallowed, DO NOT induce vomiting. If too much is breathed, remove to fresh air. For severe overexposure, call a physician immediately. For additional information, consult the Material Safety Data Sheet for this product. **DISPOSAL:** All used and unused product should be disposed of in conformance with local, state and federal regulations. Do not dump in sewers, on the ground, or into any body of water. **KEEP AWAY FROM CHILDREN**

SPECIAL USAGE WARNINGS: Contents Extremely Flammable. Do not smoke while spraying. Extinguish all flames, pilot lights, and heaters. Do not use on energized equipment. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until vapors are gone.

ELECTRICAL SHOCK HAZARD: This can will conduct electricity. Keep away from all live electrical sources including Battery Terminals, Solenoids, Electrical Panels and other electronic components. DO NOT use with ignition in "ON" position. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

Manufactured for: NAPA

Corporate Office: Atlanta, GA 30339

©2009 CRC Industries, Inc., Warminster, PA 18974

Made in U.S.A.

800-521-3168 (Technical Information)

800-272-8963 (Customer Service)

CRC#519C 09B



Heavy Duty Silicone™

Multi-Use Lubricant

Lubrificante multiuso

Stops Sticking, Binding, Squeaking on Nylon, Rubber, Metal & Wood Surfaces

DANGER: EXTREMELY FLAMMABLE. HARMFUL OR FATAL IF SWALLOWED. EYE AND SKIN IRRITANT. CONTENTS UNDER PRESSURE. READ WARNINGS ON BACK PANEL.

Net Wt. 7.5 oz. (213 g) **No. 091422**