



**POWER**  
**LUBE**<sup>®</sup>

*Multi-Purpose Lubricant*

Lubrificante multiuso

**Fights Corrosion • Loosens Rusted Parts**  
**Penetrates Fast • Stops Squeaks**  
**OK For Use In All States**

**DANGER:** HARMFUL OR  
FATAL IF SWALLOWED.

Read warnings on back panel.

No. 091849

Net Contents: 1 gal. (3.78L)

# POWER LUBE®

**APPLICATIONS:** Alternators, Cables, Cams, Carburetors, Door Handles and Locks, Engines, Generators, Ignition Systems, Seat Tracks, Spark Plugs, Springs, Wheels, Windshield Wiper Hardware.

**WARNING:** Contains Petroleum Distillates 64742-47-8 & 64741-88-4, Butyl Stearate 123-95-5, Fatty Acid Ester 61791-48-8 and Petrolatum 8009-03-8. Product should be kept from all flames and other ignition sources. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. Overexposure to liquid or vapors can cause eye and skin irritation, irritation to upper respiratory tract, and central nervous system effects such as headache, dizziness, drowsiness or confusion. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. Vapors are heavier than air and can accumulate in low areas. If you experience any symptoms listed on this label, increase ventilation or leave the area. Product may pose an aspiration hazard if swallowed.

**FIRST AID:** In case of eye or skin contact, flush with water for 15 minutes. If swallowed, DO NOT induce vomiting. If too much is breathed, remove to fresh air. For severe overexposure, call physician immediately. For additional information, consult MSDS for this product.

**DISPOSAL:** All used and unused product should be disposed of in conformance with local, state and federal regulations. Do not dump in sewers, floor drains, on the ground, or into any body of water.

**HANDLING AND SPILL PRECAUTIONS:** Keep container closed when not in use. Wash thoroughly after handling. Do not enter where high vapor concentrations are suspected unless air-supplied respirator is used and a trained observer is present and equipped with rescue gear. For spill clean-up, use proper protective equipment. Use absorbent and store in closed containers for proper disposal. Do not store above 100°F.

**KEEP AWAY FROM CHILDREN**

**DIRECTIONS:** Read entire label before using this product.

Do not apply while equipment is energized.

**STOPS SQUEAKS** – POWER LUBE® lubricates and silences annoying squeaks and squeals, reduces friction, and makes things work again. POWER LUBE® leaves a transparent protective film that guards against corrosion.

**DIRECTIONS:** Apply directly onto mechanism. No need for disassembly.

**PROTECTS METALS** – POWER LUBE® seals out rust and corrosion and keeps working to protect tools, equipment, and all metals.

**DIRECTIONS:** Apply light, even film over entire surface.

**FREES RUSTED PARTS** – POWER LUBE® penetrates quickly into threads, cracks, and crevices to make tough-to-budge lugs, nuts, bolts, and fasteners slip right off. **DIRECTIONS:** Apply liberally and allow to run off.

**STARTS WET ENGINES** – POWER LUBE® drives moisture out of wet electrical systems and keeps it out.

**DIRECTIONS:** Remove distributor cap and apply directly into distributor. Then, apply a light coating over the entire electrical system.

Safe on most plastics

Manufactured for: NAPA  
Corporate Office: Atlanta, GA 30339  
©2009 CRC Industries, Inc.  
Warminster, PA 18974  
800-521-3168 (Technical Info)  
800-272-8963 (Customer Service)  
Made in U.S.A. CRC#462D 09A

