


Eastwood

DO THE JOB **RIGHT.**

PRETM PAINTING PREP



Removes Silicone, Wax,
Polish, Grease, and Dirt
Ensures Better
Paint Adhesion
Safe for All
Metal Surfaces

DANGER – FLAMMABLE.
HARMFUL OR FATAL IF SWALLOWED.
VAPORS HARMFUL.

See other cautions on back panel.

Net Contents: 30 fl. oz. / 1 pt. 14 fl. oz. / 888 ml

10194 ZP

EASTWOOD PRE™ PAINTING PREP is designed to remove harmful contaminants that cause paint imperfections. Unlike other harsh degreasers and parts cleaners, PRE has the right formulation to remove impurities, yet be safe on the surface to be painted. PRE effectively removes wax, silicone, grease and dirt while ensuring excellent paint adhesion. PRE is ideal for paint and powder coating preparation.

DIRECTIONS – READ ALL INSTRUCTIONS BEFORE USING THIS PRODUCT

1. Test a small area to make sure PRE is compatible with the metal surface to be cleaned. PRE may damage uncured paints and may damage some plastics. **2.** Wet a clean cloth with PRE or using a trigger spray bottle, spray directly onto the surface to be cleaned. **3.** Wipe surface with a clean cloth to remove debris. Do not reuse dirty cloths. **4.** On a waxed surface use PRE before any sanding is done. **5.** Some contaminants may require multiple applications.

DISPOSAL: All used and unused product should be disposed of in accordance with local, state, and federal regulations. DO NOT dump in sewers, floor drains, on the ground, or into any body of water.

CONTAINS: Toluene 108-88-3, Xylene 1330-20-7, Ethyl Benzene 100-41-4, Petroleum Distillates 8052-41-3. Vapor Harmful. May affect the brain or nervous system causing dizziness, headache, or nausea. Causes eye, skin, nose, and throat irritation. Heat or prolonged exposure to sun may cause bursting. Do not store at temperatures above 120°F. **NOTICE:** Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. **Vapors May Ignite Explosively.** Keep away from heat, sparks, and flame. Do not smoke. Extinguish all flames and pilot lights and turn off stoves, heaters, electric motors, and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening windows and doors to achieve cross-ventilation. Use Only With Adequate Ventilation. Do not breathe dust, vapors, or spray mist. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA approved) or leave the area. Close container after each use. Avoid contact with eyes, skin, and clothing. **FIRST AID:** If swallowed, DO NOT induce vomiting. Call a physician immediately. If it becomes difficult to breath, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention. For skin, wash thoroughly with soap and water.

KEEP OUT OF THE REACH OF CHILDREN

Not for use in California. For additional information, consult the Safety Data Sheet (SDS) for this product. 100% VOC.

**Only in the Event of a Chemical Emergency Involving a Spill, Leaks, Fire, or Exposure, Call Chemtrec Toll-Free, Day or Night:
1-800-424-9300 International Call Collect: (202) 483-7616.**

Manufactured for The Eastwood Company, 263 Shoemaker Road, Pottstown, PA 19464
USA: 1-800-345-1178 Canada: 1-800-820-9042 International: (610) 323-2200
www.eastwood.com © Copyright 2012 Easthill Group, Inc. Made in USA



Scan for product info



Label #10194ZPL • Rev. 8/12
©Copyright 2012 The Easthill Group, Inc.