



CRC

10 MINUTE

Radiator Flush

One-Step Non-Acid Cleaner

WARNING: MAY CAUSE EYE IRRITATION.
READ WARNINGS ON BACK PANEL.

PART NO. 095337
Net Contents 12 fl. oz. (355 mL)

NAPA/CRC RADIATOR FLUSH

For use in all cooling systems, including aluminum. Harmless to metal and rubber parts when used as directed. Quickly removes grease, oil and rust.

DIRECTIONS: Read entire label before use. 1. Drain cooling system completely. Close petcocks. Fill system with fresh water and empty contents of container into radiator. 2. Replace radiator cap, but do not tighten. Turn only to first notch. 3. Run engine for 10 minutes, after reaching normal operating temperature. 4. Stop engine and drain radiator. Refill with water. **DO NOT ADD COLD WATER TO HOT SYSTEM.** 5. Run engine 5 minutes. Drain radiator. Refill with radiator coolant. Add NAPA/CRC Radiator Anti-Rust #095335 to prevent new rust.

WARNING: Contains Water 7732-18-5 and Tallowamine 68155-39-5. Avoid continuous breathing of vapors. Avoid contact with skin and eyes. **FIRST AID:** In case of eye or skin contact, flush with large amounts of water for at least 15 minutes. If swallowed, do not induce vomiting. If too much is breathed, remove to fresh air. For severe overexposure, call a physician immediately.

KEEP AWAY FROM CHILDREN.

All used and unused product should be disposed of in conformance with local, state, and federal regulations. For additional information, consult the Material Safety Data Sheet for this product.

Manufactured for: NAPA
Corporate Office: Atlanta, GA 30339
Made in U.S.A.
CRC#613A

© 2001 CRC Industries, Inc.
Warminster, PA 18974
800-521-3168 (Technical Information)
800-272-8963 (Customer Service)
01A

