



# Diesel Recovery Emergency Fuel Treatment

Part No. 09543



**DRC55**

**NET WEIGHT 355 lbs. (161.4 Kg)**

This diesel fuel additive complies with the federal ultra-low sulfur content requirements for use in all diesel motor vehicles and non-road engines.

**HANDLING AND SPILL PRECAUTIONS:** Keep container closed. Do not store bulk container above 80°. Wash thoroughly after handling. Do not enter where vapors are suspected in high concentration unless air supplied positive pressure breathing apparatus is used and a trained observer is present and equipped with rescue gear. **FOR SPILLS,** use proper protective equipment. Take precautions as necessary to prevent contamination of ground or surface water. For small spills, use absorbent and sweep into closed containers for disposal. For large spills, evacuate the area, dike and transfer into containers for disposal. **DISPOSAL:** Used and unused contents and containers must be disposed of in accordance with all federal, state, and local regulations. **EMPTY** containers may be offered to a qualified reconditioner. Unused contents may be offered to a licensed reclaimer. Do not dump into sewers, on the ground, or into any body of water.

**DIRECTIONS: Read entire label before using this product.**

- 1 Remove the existing fuel filter or obtain a new fuel filter.
- 2 Fill fuel filter with AMSOIL Diesel Recovery Emergency Fuel Treatment.
- 3 Reinstall fuel filter.
- 4 Add remaining contents of the bottle to the fuel tank and add more if required by treat rate recommendations.  
Treat Rate: One gallon of AMSOIL Diesel Recovery Emergency Fuel Treatment to every 128 gallons of fuel (one quart treats 32 gallons of fuel). Additional treatment may be required if equipped with larger fuel tanks.
- 5 Start the engine and allow the fuel system to circulate until full power has been restored to the engine.

**FIRST AID:** In case of eye or skin contact, flush with water for 15 minutes. If swallowed, **DO NOT** induce vomiting. If too much is breathed, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. For severe overexposure, call a physician immediately.

**CAUTION:** Empty containers retain residue (liquid and/or vapor) and can be dangerous. **DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND OR EXPOSE THIS CONTAINER TO HEAT, FLAME, SPARKS, OR OTHER SOURCES OF IGNITION: IT MAY EXPLODE AND CAUSE INJURY OR DEATH.** Do not attempt to clean, since residue is difficult to remove. Empty drums should be completely drained, promptly bunged, and promptly returned to a drum reconditioner.

Use only in a well ventilated area. This product contains chemicals known to the State of California to cause cancer, birth defects and other reproductive harm. For additional information, consult the Material Safety Data Sheet for this product.

**KEEP AWAY FROM CHILDREN**

**DANGER: COMBUSTIBLE. HARMFUL OR FATAL IF SWALLOWED.**  
Read warnings carefully.

**WARNING:** Contains Stoddard Solvent 8052-41-3, Petroleum Naphtha 64742-94-5, Tetramethylbenzene 527-53-7 and Naphthalene 91-20-3.

©2010 Amsoil  
Superior, WI 54886  
715-392-7101  
[www.Amsoil.com](http://www.Amsoil.com)  
Batch  
Date Code  
10A CRC#673C  
Made in U.S.A.  
FOR EMERGENCIES  
CALL CHEMTREC  
1-800-424-9300

HEALTH	<b>2</b>	REACTIVITY	<b>0</b>
FLAMMABILITY	<b>2</b>	PERSONAL PROTECTION	<b>B</b>

HAZARD: MINIMAL=0 SEVERE=4